



Hilti (Canada) Corporation

MSDS No.: 102C
Revision No.: 007
Prep. Date: Jan 9, 2014
Page: 1 of 2

(10408)

MATERIAL SAFETY DATA SHEET

Product identifier: Spray Lubricant
Product description / use: Petroleum-derivatives / Spray lubricant for cleaning Hilti powder actuated tools
Supplier: Hilti (Canada) Corporation, 2360 Meadowpine Blvd., Mississauga, Ontario L5N 6S2
Originator: Hilti, Inc., P. O. Box 21148, Tulsa, Oklahoma, USA 74121
Emergency phone number: Chem-Trec: 1 800 424 9300

INGREDIENTS INFORMATION

Ingredient	CAS Number	% (wt.)	LC ₅₀ (rat)	LD ₅₀ (rat)	TLV	STEL
------------	------------	---------	------------------------	------------------------	-----	------

Not a hazardous chemical as defined by the Controlled Products Regulations SOR/88-66

PHYSICAL PROPERTIES

Appearance / Physical state:	Clear liquid.	Odour:	Mild oil-like odour.
Specific gravity (at 20°C):	0.94	Odour threshold:	Not determined.
Vapour pressure (at 20°C):	Not applicable.	Vapour density:	Not applicable.
Evaporation rate:	Not determined.	Boiling point:	Not determined.
Freezing point:	Not determined.	pH:	Not determined.
Coefficient of H₂O / oil distrib:	Not determined.	Solubility in water:	Slightly soluble.

FIRE AND EXPLOSION DATA

Flash point / Method:	> 215 C / DIN 53213	Flammable limits:	Not applicable.
Conditions of flammability:	Exposure to direct flame.	Auto-ignition temperature:	Not applicable.
Means of extinction:	CO ₂ , Dry Chemical, Foam.		
Special fire fighting procedures:	None known. A NIOSH-approved self-contained breathing apparatus (SCBA) should be worn when fighting fires involving chemicals.		
Hazardous combustion products:	Normal products of combustion are expected including CO and CO ₂ .		
Sensitivity to mechanical impact / static discharge:	Not susceptible to mechanical impact or to a static discharge.		

REACTIVITY DATA

Stability:	Stable.	Conditions of reactivity:	None known.
Incompatible materials:	Strong oxidizing agents.		
Hazardous decomposition products:	None known. Thermal decomposition can yield oxides of carbon.		

TOXICOLOGICAL PROPERTIES

Routes of exposure:	<input type="checkbox"/> N/Ap <input checked="" type="checkbox"/> Skin contact <input type="checkbox"/> Skin absorption <input checked="" type="checkbox"/> Eye contact <input type="checkbox"/> Inhalation <input type="checkbox"/> Ingestion		
Exposure limits:	None established. See "Ingredients" section above.		
Acute effects of exposure:	Eyes - Slight irritation is possible. Corneal injury is not expected. Skin - No effects expected. Irritation is possible with some individuals. Inhalation - No effects expected. Ingestion - Not a likely route of exposure. Effects of ingestion have not been determined. Considered to have a low acute oral toxicity.		
Chronic effects of exposure:	None known.		
Synergistic materials:	None known.		

APPROVED MATERIAL

APR 27 2014

MSDS # 10408

APPROVED BY *[Signature]*

FIRST AID MEASURES

Eyes:	Flush with plenty of water. Call a physician if symptoms occur.
Skin:	Wash with soap and water. Seek medical attention if any effects persist.
Inhalation:	No ill effects expected. Should discomfort occur, move to fresh air.
Ingestion:	Not a likely route of exposure. Do not induce vomiting unless recommended by a physician. Seek medical attention immediately.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure

PREVENTIVE MEASURES

Engineering controls:	General (natural or mechanically induced fresh air movements).
Eye protection:	Safety glasses with side shields are recommended.
Skin protection:	Impermeable gloves recommended.
Respiratory protection:	None normally required.
Other:	No additional measures are normally required.
Handling procedures and equipment:	For industrial use only. Do not heat can or expose to direct flame. Do not get into the eyes. Avoid prolonged or repeated contact with the skin. Practice good hygiene; i.e., wash after using and before eating or smoking.
Storage requirements:	Keep out of reach of children. Store in a cool dry place out of direct rays of the sun. Recommended storage temperature range is between 5° and 30° C.
Spill, leak or release:	Wipe away spilled material with a cloth or other absorbent material. Place in a container for proper disposal in accordance with all applicable local, state, or federal requirements. Do not allow into waterways.
Waste disposal:	Consult with regulatory agencies or your corporate personnel for disposal methods that comply with local, provincial, and federal safety, health and environmental regulations.
Special shipping instructions:	None known.

REGULATORY INFORMATION

WHMIS classification:	Not a controlled product according to WHMIS definitions
HMIS codes:	Health 0, Flammability 0, Reactivity 0, PPE B
TDG shipping name:	Not regulated.

PREPARATION INFORMATION / CONTACTS

Prepared by:	Hilti, Inc., Tulsa, OK USA	Date of Preparation:	Jan. 9, 2014	Emergency phone number:	1 800 424 9300
Customer Service:	Hilti (Canada) Corporation, Mississauga, Ontario; 1 800 363 4458				
Health / Safety contacts:	Hilti, Inc., Tulsa, OK USA; 1 800 879 6000, Jerry Metcalf (x1003704)				
Abbreviations used:	N/E = None Established. N/Ap = Not Applicable. N/Av = Not Available. HMIS: Hazardous Materials Identification System				

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.