

(10566)



# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

**Product ID:** 610B6  
**Product Name:** D.T.M. ATA0009 BLACK  
**Product Use:** Paint product.  
**Effective date:** 13/Aug/2011  
**Revision Date:** 13/Aug/2011  
**UN ID Number (msds):** UN1263  
**WHMIS Classification:** D2B Toxic Material D2A Very Toxic Material B2 Flammable Liquids

### Company Identification

Valspar, Inc.  
1915 Second Street West  
Cornwall, Ontario K6H 5T1

**Tech Info Phone:** 1-613-932-8960

**24-Hour Medical Emergency  
Phone:** 1-888-345-5732

## 2. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

### Eye Contact:

- Moderate eye irritation

### Skin Contact:


- Causes skin irritation.
- May cause defatting of the skin.

### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

### Inhalation:

- Causes respiratory tract irritation.



- Harmful by inhalation.

**Target Organ and Other Health Effects:**

- Causes headache, drowsiness or other effects to the central nervous system.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Carcinogens:**

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name	CAS Number
BARIUM SULPHATE 7727-43-7	40 - 45	Barium sulfate	7727-43-7
STODDARD SOLVENT 8052-41-3	10 - 15	Stoddard solvent	8052-41-3
BUTYL ACETATE 123-86-4	5 - 10	n-Butyl acetate	123-86-4
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	Ethyl 3-ethoxypropionate	763-69-9
METHYL PROPYLKETONE 107-87-9	1 - 5	Methylpropyl ketone	107-87-9
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	Carbon black	1333-86-4

If this section is blank there are no hazardous components per WHMIS guidelines.

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.**

**4. FIRST AID MEASURES**

**Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	45
Flash point (Celsius):	7
Lower explosive limit (%):	1
Upper explosive limit (%):	9
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

### Unusual fire and explosion hazards:

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

### Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

## 7. HANDLING AND STORAGE

### Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Chemical goggles, also wear a face shield if splashing hazard exists.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### Other Personal Protection Data:

Usual industrial work clothes.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
BARIUM SULPHATE 7727-43-7	40 - 45	5 mg/m <sup>3</sup> TWA respirable fraction		
STODDARD SOLVENT 8052-41-3	10 - 15	2900 mg/m <sup>3</sup> TWA 500 ppm TWA		
BUTYL ACETATE 123-86-4	5 - 10	150 ppm TWA 710 mg/m <sup>3</sup> TWA		
METHYL PROPYLKETONE 107-87-9	1 - 5	200 ppm TWA 700 mg/m <sup>3</sup> TWA		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup> TWA		

**ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
BARIUM SULPHATE 7727-43-7	40 - 45	10 mg/m <sup>3</sup> TWA			
STODDARD SOLVENT 8052-41-3	10 - 15	100 ppm TWA			
BUTYL ACETATE 123-86-4	5 - 10	150 ppm TWA	200 ppm STEL		
METHYL PROPYLKETONE 107-87-9	1 - 5	200 ppm	150 ppm STEL		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup> TWA			

**9. PHYSICAL PROPERTIES**

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	27 mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	5.0
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	12.23
Specific Gravity:	1.47
Evaporation rate (butyl acetate = 1.0):	2.3
Flash point (Fahrenheit):	45

## 9. PHYSICAL PROPERTIES

Flash point (Celsius):	7
Lower explosive limit (%):	1
Upper explosive limit (%):	9
Autoignition temperature:	not determined

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Oxides of sulfur.

**Sensitivity to static discharge:** Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
BUTYL ACETATE 123-86-4	5 - 10	= 10768 mg/kg Oral LD50 Rat = 390 ppm Inhalation LC50 Rat 4 h > 17600 mg/kg Dermal LD50 Rabbit
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	= 10 mL/kg Dermal LD50 Rabbit = 3200 mg/kg Oral LD50 Rat
METHYL PROPYLKETONE 107-87-9	1 - 5	= 1600 mg/kg Oral LD50 Rat = 6500 mg/kg Dermal LD50 Rabbit
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	> 15400 mg/kg Oral LD50 Rat > 3 g/kg Dermal LD50 Rabbit

### Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

IARC has classified carbon black as possibly carcinogenic to humans (Group 2B).

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1			Monograph 65 [1996]

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	Present		

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

### 13. DISPOSAL CONSIDERATIONS

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

### 14. TRANSPORTATION INFORMATION

#### Canadian Transport of Dangerous Goods

Proper Shipping Name: PAINT  
Hazard Class: 3  
UN ID Number (msds): UN1263  
Packing Group: II

#### TDG Clear Language Exceptions:

For Dangerous Goods, the supplier may apply one of the following exceptions (TDG Reference): Limited quantity/Consumer Commodity (1.17), Does not sustain combustion, etc. (2.18), Viscous liquid (2.19), Flammable liquid General Exemption (1.33) or US DOT Reciprocity (9.1,3 & 4). Please consult current TDG regulations before applying any of these exceptions to subsequent shipments.

#### International Air Transport Association (IATA):

Proper Shipping Name: Paint  
Hazard Class: 3  
UN ID Number (msds): UN1263  
Packing Group: II

#### International Maritime Organization (IMO):

Proper Shipping Name: PAINT  
Hazard Class: 3  
IMO UN/ID Number (msds): UN1263  
Packing Group: II

### 15. REGULATORY INFORMATION

#### INTERNATIONAL REGULATIONS - Chemical Inventories

##### Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

##### US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

##### Canada National Pollutant Release Inventory:

Ingredient Name CAS-No.	Approx. Weight %	NPRI Status
STODDARD SOLVENT 8052-41-3	10 - 15	Part 5 Substance
BUTYL ACETATE 123-86-4	5 - 10	Part 5 Substance
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	Part 4 Substance
METHYL PROPYLKETONE 107-87-9	1 - 5	Part 4 Substance

## 16. OTHER INFORMATION

### HMIS Codes

Health:	2*
Flammability:	3
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

### Preparation Information:

Prepared By:	Regulatory Affairs Department
Print date:	13/Aug/2011
Revision Date:	13/Aug/2011

### Technical Information:

The Valspar Corporation	
PO Box 1461	
Minneapolis, MN 55440	
Tech Info Phone:	1-613-932-8960

<b>24-Hour Medical Emergency Phone:</b>	<b>1-888-345-5732</b>
---	-----------------------