



if it matters, we're on it.®

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: ELW0002
Product Name: R-CURE 420 EPOXY WHITE
Product Use: Paint or Coatings Related Product
Effective date: 27/Jan/2012
Revision Date: 27/Jan/2012
UN ID Number (msds): UN1263
WHMIS Classification: D2B Toxic Material D2A Very Toxic Material B2 Flammable Liquids

Company Identification

Valspar, Inc.
 1915 Second Street West
 Cornwall , Ontario K6H 5T1

Tech Info Phone: 1-613-932-8960

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:


Inhalation
 Ingestion
 Skin absorption

Eye Contact:

- Severe eye irritation
- Risk of serious damage to eyes.

Skin Contact:

- Causes skin irritation.
- Dermatitis
- May cause defatting of the skin.
- Harmful if absorbed through skin.
- May cause sensitization by skin contact.



Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause chemical pneumonia.
- May cause damage to nasal and respiratory passages.
- May cause sensitization by inhalation.
- May cause pulmonary edema.

Target Organ and Other Health Effects:

- Kidney injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Liver injury may occur.
- Unconsciousness

This product contains ingredients that may contribute to the following potential chronic health effects:

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Prolonged exposure over TLV may produce pneumoconiosis.
- Contains formaldehyde which is considered a potential carcinogen by the Occupational Health and Safety Administration.
- Possible sensitization.
- Systemic toxicity

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name	CAS Number
TALC 14807-96-6	30 - 35	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6
METHYL ETHYL KETONE 78-93-3	15 - 20	Methyl ethyl ketone	78-93-3
TITANIUM DIOXIDE 13463-67-7	10 - 15	Titanium dioxide	13463-67-7
EPOXY RESIN 25036-25-3	5 - 10	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	25036-25-3
BARIUM SULPHATE 7727-43-7	1 - 5	Barium sulfate	7727-43-7
BUTYL ACETATE 123-86-4	1 - 5	n-Butyl acetate	123-86-4

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

METHYL ISOBUTYL KETONE 108-10-1	1 - 5	Methylisobutyl ketone	108-10-1
ETHYLBENZENE 100-41-4	.1 - 1	Ethyl benzene	100-41-4

If this section is blank there are no hazardous components per WHMIS guidelines.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

4. FIRST AID MEASURES

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	45
Flash point (Celsius):	7
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid all personal contact.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

Skin protection:

Gloves: Neoprene or other nonporous.

Other Personal Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas. Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant apron

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TALC 14807-96-6	30 - 35	Respirable. Listed. Total dust. Listed.		
METHYL ETHYL KETONE 78-93-3	15 - 20	200 ppm TWA 590 mg/m ³ TWA		
TITANIUM DIOXIDE 13463-67-7	10 - 15	15 mg/m ³ TWA dust total		
BARIUM SULPHATE 7727-43-7	1 - 5	5 mg/m ³ TWA respirable fraction		

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
BUTYL ACETATE 123-86-4	1 - 5	150 ppm TWA 710 mg/m ³ TWA		
METHYL ISOBUTYL KETONE 108-10-1	1 - 5	100 ppm TWA 410 mg/m ³ TWA		
ETHYLBENZENE 100-41-4	.1 - 1	100 ppm TWA 435 mg/m ³ TWA		

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TALC 14807-96-6	30 - 35	2 mg/m ³ TWA respirable fraction, particulate matter containing no asbestos and <1% crystalline silica			
METHYL ETHYL KETONE 78-93-3	15 - 20	200 ppm TWA	300 ppm STEL		
TITANIUM DIOXIDE 13463-67-7	10 - 15	10 mg/m ³ TWA			
BARIUM SULPHATE 7727-43-7	1 - 5	10 mg/m ³ TWA			
BUTYL ACETATE 123-86-4	1 - 5	150 ppm TWA	200 ppm STEL		
METHYL ISOBUTYL KETONE 108-10-1	1 - 5	50 ppm TWA	75 ppm STEL		
ETHYLBENZENE 100-41-4	.1 - 1	100 ppm TWA	125 ppm STEL		

9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	75.9398496 mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	4
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	12.19
Specific Gravity:	1.46
Evaporation rate (butyl acetate = 1.0):	5.7
Flash point (Fahrenheit):	45
Flash point (Celsius):	7
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined

10. STABILITY AND REACTIVITY

10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Conditions to Avoid:

Heat.

Incompatibility:

Strong oxidizing agents

Hazardous Polymerization:

None anticipated.

Hazardous Decomposition Products:

Silicon dioxide. Carbon monoxide and carbon dioxide.
Metal oxide fumes.

Sensitivity to static discharge:

Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
METHYL ETHYL KETONE 78-93-3	15 - 20	= 2737 mg/kg Oral LD50 Rat = 32 g/m ³ Inhalation LC50 Mouse 4 h = 6480 mg/kg Dermal LD50 Rabbit
TITANIUM DIOXIDE 13463-67-7	10 - 15	> 10000 mg/kg Oral LD50 Rat
BUTYL ACETATE 123-86-4	1 - 5	= 10768 mg/kg Oral LD50 Rat = 390 ppm Inhalation LC50 Rat 4 h > 17600 mg/kg Dermal LD50 Rabbit
METHYL ISOBUTYL KETONE 108-10-1	1 - 5	= 2080 mg/kg Oral LD50 Rat = 8.2 mg/L Inhalation LC50 Rat 4 h > 16000 mg/kg Dermal LD50 Rabbit
ETHYLBENZENE 100-41-4	.1 - 1	= 15354 mg/kg Dermal LD50 Rabbit = 17.2 mg/L Inhalation LC50 Rat 4 h = 3500 mg/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

Possible mutagen

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans. Contains TIO₂ which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO₂ provide an adequate basis to conclude TIO₂ is carcinogenic. TIO₂ is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
ETHYLBENZENE 100-41-4	.1 - 1		Listed. initial date 6/11/04 - carcinogen

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
TITANIUM DIOXIDE 13463-67-7	10 - 15			Monograph 47 [1989]
ETHYLBENZENE 100-41-4	.1 - 1			Monograph 77 [2000]

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
TALC 14807-96-6	30 - 35			male rat-some evidence; female rat-clear evidence; male mice-no evidence; female mice- no evidence
TITANIUM DIOXIDE 13463-67-7	10 - 15			male rat-negative; female rat-negative; male mice-negative; female mice-negative
METHYL ISOBUTYL KETONE 108-10-1	1 - 5			male rat-some evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence
ETHYLBENZENE 100-41-4	.1 - 1			male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	10 - 15	Present		
ETHYLBENZENE 100-41-4	.1 - 1	Present		A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

Canadian Transport of Dangerous Goods

Proper Shipping Name: PAINT
Hazard Class: 3
UN ID Number (msds): UN1263
Packing Group: II

TDG Clear Language Exceptions:

For Dangerous Goods, the supplier may apply one of the following exceptions (TDG Reference): Limited quantity/Consumer Commodity (1.17), Does not sustain combustion, etc. (2.18), Viscous liquid (2.19), Flammable liquid General Exemption (1.33) or US DOT Reciprocity (9.1,3 & 4). Please consult current TDG regulations before applying any of these exceptions to subsequent shipments.

International Air Transport Association (IATA):

Proper Shipping Name: Paint
 Hazard Class: 3
 UN ID Number (msds): UN1263
 Packing Group: II

International Maritime Organization (IMO):

Proper Shipping Name: PAINT
 Hazard Class: 3
 IMO UN/ID Number (msds): UN1263
 Packing Group: II

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS - Chemical Inventories

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada National Pollutant Release Inventory:

Ingredient Name CAS-No.	Approx. Weight %	NPRI Status
METHYL ETHYL KETONE 78-93-3	15 - 20	Part 1, Group 1 Substance Part 5 Substance Part 1, Group 1 Substance
BUTYL ACETATE 123-86-4	1 - 5	Part 5 Substance
METHYL ISOBUTYL KETONE 108-10-1	1 - 5	Part 1, Group 1 Substance Part 5 Substance Part 1, Group 1 Substance
ETHYLBENZENE 100-41-4	.1 - 1	Part 1, Group 1 Substance

16. OTHER INFORMATION

HMIS Codes

Health: 2*
 Flammability: 3
 Reactivity: 1
 PPE: X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By: Regulatory Affairs Department
Print date: 27/Jan/2012
Revision Date: 27/Jan/2012

Technical Information:

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440
Tech Info Phone: 1-613-932-8960

**24-Hour Medical Emergency
Phone:** 1-888-345-5732