

(10799)

Material Safety Data Sheet



Revision Number: 007.2

Issue date: 02/03/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	Loctite(R) 587 Blue High Performance RTV Silicone Gasket Maker	IDH number:	135504
Product use:	Silicone rubber sealant	Item number:	58730
		Region:	Canada
Company address:	Contact information:		
Henkel Corporation	Telephone: 905.814.6511		
2225 Meadowpine Boulevard	Emergency telephone: 905.814.6511		
Mississauga, Ontario L5N 7P2	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
Physical state:	paste
Color:	blue
Odor:	mild, Petroleum
	WHMIS hazard class: D.2.A, D.2.B
WARNING:	<p>PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.</p> <p>PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE BURNS TO SKIN AND EYES.</p> <p>REPEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC SKIN REACTION.</p>


Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	The silane is a skin and eye irritant and prolonged contact may cause eye and skin burns. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Skin contact:	Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization reaction. Possible burns to skin.
Eye contact:	Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion:	Not expected under normal conditions of use. May be harmful if swallowed.

Existing conditions aggravated by exposure: Skin disorders.

See Section 11 for additional toxicological information.



3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Siloxanes and Silicones, di-Me, hydroxy-terminated	70131-67-8	30 - 60
Limestone	1317-65-3	30 - 60
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	2224-33-1	1 - 5
Aluminum	7429-90-5	0.1 - 1
3-(Trimethoxysilyl)propylamine	13822-56-5	0.1 - 1
White mineral oil (petroleum), highly refined	8042-47-5	0.1 - 1
Butanone oxime	96-29-7	0.1 - 1
Quartz (SiO ₂)	14808-60-7	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. If symptoms develop and persist, get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 93 °C (> 199.4 °F) Tagliabue closed cup
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Dry chemical. foam Carbon dioxide.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of silicon. Formaldehyde.
Sensitivity to Mechanical Impact:	Not available.
Sensitivity to static discharge:	Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.

Storage: For safe storage, store at or below 32 °C (89.6 °F)
Keep container closed.

For information on product shelf life contact Henkel Canada Customer Service at (905) 814-6511.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Siloxanes and Silicones, di-Me, hydroxy-terminated	None	None	None	None
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	None	None	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA (as Al) Total dust. 5 mg/m3 TWA (as Al) Respirable dust.	None	None
3-(Trimethoxysilyl)propylamine	None	None	None	None
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 TWA Mist.	None	None
Butanone oxime	None	None	10 ppm (36 mg/m3) TWA (Skin sensitizer.)	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves. Impervious clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: paste
Color: blue
Odor: mild, Petroleum
Odor threshold: Not available.
pH: Not applicable
Vapor pressure: < 5 mm hg (20 °C (68°F))
Boiling point/range: Not available.
Melting point/ range: Not available.
Specific gravity: 1.31 at 20 °C (68°F)
Vapor density: Not available.

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup
 Flammable/Explosive limits - lower: Not available.
 Flammable/Explosive limits - upper: Not available.
 Autoignition temperature: Not available.
 Evaporation rate: Not available.
 Solubility in water: Polymerises in presence of water.
 Partition coefficient (n-octanol/water): Not available.
 VOC content: 3.33 %; 43.09 g/l

10. STABILITY AND REACTIVITY

Stability: Stable
 Hazardous reactions: Will not occur.
 Hazardous decomposition products: Oxides of carbon. Oxides of silicon. Formaldehyde Methyl ethyl ketoxime formed during cure.
 Incompatible materials: Acids. Bases. Oxidizing agents. Polymerizes on contact with water.
 Conditions to avoid: Moisture.

11. TOXICOLOGICAL INFORMATION

Toxicologically synergistic products: Not available.

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Siloxanes and Silicones, di-Me, hydroxy-terminated	No	No	No	No
Limestone	No	No	No	No
Butan-2-one O,O',O''-(vinylsilyldyne)trioxime	No	No	No	No
Aluminum	No	No	No	Group A4
3-(Trimethoxysilyl)propylamine	No	No	No	No
White mineral oil (petroleum), highly refined	No	No	No	Group A4
Butanone oxime	No	No	No	No
Quartz (SiO ₂)	Known To Be Human Carcinogen.	Group 1	No	Group A2

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Siloxanes and Silicones, di-Me, hydroxy-terminated	None	No Target Organs
Limestone	None	Nuisance dust
Butan-2-one O,O',O''-(vinylsilyldyne)trioxime	None	Irritant, Allergen
Aluminum	None	Central nervous system, Irritant, Lung
3-(Trimethoxysilyl)propylamine	None	Irritant, Allergen
White mineral oil (petroleum), highly refined	None	Irritant
Butanone oxime	None	Allergen, Blood, Central nervous system, Eyes, Irritant, Some evidence of carcinogenicity
Quartz (SiO ₂)	None	Immune system, Lung, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Cured rubber can be incinerated or landfilled following EPA and local regulations.

14. TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Exceptions:	None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.