

(10955)

MATERIAL SAFETY DATA SHEET

PAGE 1 OF 4

DATE PREPARED: JUNE 01/06

REVISED: April 2/2012

SECTION: 1

MANUFACTURER:

PRODUCT IDENTIFICATION

Strike First Corporation
c/o Steel Fire Equipment
150 Superior Blvd.
Mississauga, ON
L5T 2L2
Phone: 1-905-564-1500

ABC SUPER 90 DRY CHEMICAL
Multi-Purpose Dry Chemical
Fire Extinguisher

EMERGENCY PHONE:
Canutec: 1-613-996-6666

SECTION: 2

HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS #	%	*ACGIH mg/m3		*OSHA mg/m3			OTHER
			W/W	TLV	STEL	PEL	STEL	
Mono Ammonium Phosphate	7722-76-1	95*						
Mica	12001-26-2	<3	3	NE	3	NE	NE	NE
Attaclay	8031-18-3	<3	NE	NE	NE	NE	NE	NE
Silicone Oil	63148-57-2	<1	NE	NE	NE	NE	NE	NE
Calcium Carbonate	471-34-1	<1	NE	NE	NE	NE	NE	NE
Silica	112926-00-8	<1	2	NE	6	NE	NE	NE
Yellow Pigment	5468-75-7	<1	NE	NE	NE	NE	NE	NE

*ACGIH TLV for particulars, not otherwise classified = 10; OSHA PEL for particulars not otherwise regulated, Total dust =15 Respirable fraction 5.

NE = Not established

SECTION :3

PHYSICAL DATA

BOILING POINT	Not applicable
VAPOR PRESSURE	Not applicable
VAPOR DENSITY	Not applicable
SOLUBILITY IN WATER	Not soluble. Water repellent coating.
SPECIFIC GRAVITY	Approximately 0.88
PERCENT VOLATILE BY VOLUME	Not applicable
EVAPORATION RATE	Not applicable
pH: (10% solution)	Approximately 9-10
APPEARANCE & COLOR	This material is a finely divided yellow powder.

APPROVED MATERIAL

JUL 13 2012

MSDS # 10955

APPROVED BY *[Signature]*

SECTION: 4

FIRE AND EXPLOSION DATA

FLASH POINT	Not applicable
FLAMMABLE LIMITS	Lower (LEL) Not applicable Upper (LEL) Not applicable
EXTINGUISHING MEDIA	None This product is a fire extinguishing agent.
SPECIAL FIREFIGHTING PROCEDURES	Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment.

SECTION: 5

HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	*ACGIH TLV for particulars, Not otherwise classified = 10
OSHA PEL	For particulars not otherwise regulated; Total Dust =15, Respirable Fraction 5.

EFFECTS OF OVEREXPOSURE

Acute	This extinguishing material presents only a slight risk of causing acute health effects. If such effects occur, they will be in the form of mild irritation of the skin, nose, or throat and moderate irritation of the eyes. If ingested, this product may cause an upset stomach.
Chronic	This product is not known to cause chronic illnesses or diseases.

EMERGENCY FIRST-AID PROCEDURES

SKIN EXPOSURE	If spilled on skin, immediately begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.
---------------	---

EYE EXPOSURE	If chemical is splashed in eyes, open victim's eyes while under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes.
--------------	--

SECTION: 5 **EMERGENCY FIRST-AID PROCEDURES**

INHALATION	If chemical is inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.
------------	--

SECTION: 6 **REACTIVITY DATA**

STABILITY	Stable
INCOMPATIBILITY	Strong acids. Reacts violently with lithium.
HAZARDOUS DECOMPOSITION PRODUCT	Carbon monoxide and carbon dioxide
HAZARDOUS POLYMERIZATION	Will not occur

SECTION: 7 **SPILL OR LEAK PROCEDURES**

SMALL SPILLS	Sweep up the spilled solid and place all spill residue in a double plastic bag and seal.
LARGE SPILLS	If it is determined that exposure guidelines for nuisance particulates - 10 mg/m ³ (total particulates) or 5 mg/m ³ (respirable particulates) is exceeded use Level C: triple gloves (rubber gloves with nitrile gloves, over latex gloves), chemically resistant suit and boots, hard hat, and air purifying respirator with a HEPA filter. Sweep or vacuum. Dispose of in accordance with Federal, Provincial and local hazardous waste disposal regulations.

MANUFACTURER: Strike First Corporation

PRODUCT IDENTIFICATION: ABC DRY CHEMICAL FIRE EXTINGUISHER

SECTION: 8

SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION**

Respiratory protection is not expected to be needed. Maintain airborne contaminant concentrations below guidelines for nuisance particulates: (see Section 5)

VENTILATION

Use with adequate ventilation. Use a mechanical fan or vent area to outside.

PROTECTIVE GLOVES

Wear rubber gloves for routine industrial use.

EYE PROTECTION

Safety glasses.

OTHER PROTECTIVE

Use body protection appropriate for task.

EQUIPMENT:

SECTION: 9

SPECIAL PRECAUTIONS**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

All employees who handle this material should be trained to handle it safely. Avoid breathing dusts generated by this product.

Avoid getting chemicals ON YOU or IN YOU.

OTHER PRECAUTIONS: None

SECTION: 10

TRANSPORTATION

Hazard Class or Division:

Fire Extinguisher,

Class 2.2
UN 1044

For additional information contact Strike First Corporation

No harm to the environment is expected from this preparation

Fire extinguishers are designed and produced for the specific purpose of providing a safe and efficient safety tool to be used only in the fighting of fires. Improper or careless use may cause severe bodily injury and/or property damage.

Contents are under pressure which is necessary to deliver the contained extinguishing agent to the fire source.

- Contents under pressure. Do not puncture, incinerate or discharge into another person's face.
- Do not store at high temperatures above 120 degrees Fahrenheit or 49 degrees Celcius.
- Keep away from children.
- Avoid inhaling the extinguishing agent. Avoid inhaling smoke and fumes - all fires release toxic substances that are harmful. DO NOT remain in a closed area after use: evacuate the area immediately and ventilate thoroughly before re-entering.
- Although extinguishing agents are non toxic when used properly, contact with them may cause irritation to eyes, nose, throat and other allergic symptoms.