

valspar

if it matters, we're on it.®

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 082.04C4200.076
Product Name: CAT YELLOW PAINT AEROSOL HG 12U
Product Use: Paint product.
Effective date: 06/Jan/2012
Revision Date: 24/Dec/2011
UN ID Number (msds): CONCOM
WHMIS Classification: D2B Toxic Material D2A Very Toxic Material B2 Flammable Liquids B5 Flammable Aerosols

Company Identification

Valspar, Inc.
 1915 Second Street West
 Cornwall , Ontario K6H 5T1

Tech Info Phone: 1-613-932-8960

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
 Ingestion
 Skin absorption


Eye Contact:

- Severe eye irritation
- Risk of serious damage to eyes.

Skin Contact:

- Causes skin irritation.
- May cause defatting of the skin.

Ingestion:



- Irritation of the mouth, throat, and stomach.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- Asphyxia

Acute Other Health Effects:

- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause frostbite

Target Organ and Other Health Effects:

- Liver injury may occur.
- Cardiac arrhythmias
- Causes headache, drowsiness or other effects to the central nervous system.
- Kidney injury may occur.
- Blood disorders

This product contains ingredients that may contribute to the following potential chronic health effects:

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Teratogens:

- May cause birth defects.
- Female reproductive toxin.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name	CAS Number
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	Acetone	67-64-1
PROPANE 74-98-6	15 - 20	Propane	74-98-6
NAPHTHA 64742-88-7	10 - 15	SOLVENT NAPHTHA, PETROLEUM, MEDIUM ALIPH	64742-88-7
NAPHTHA 64742-89-8	5 - 10	SOLVENT NAPHTHA, PETROLEUM, LIGHT ALIPH	64742-89-8
TOLUENE 108-88-3	1 - 5	Toluene	108-88-3
TITANIUM DIOXIDE 13463-67-7	1 - 5	Titanium dioxide	13463-67-7

If this section is blank there are no hazardous components per WHMIS guidelines.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

4. FIRST AID MEASURES

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Do not give direct mouth-to-mouth resuscitation if inhaled. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	-76
Flash point (Celsius):	-60
Lower explosive limit (%):	1
Upper explosive limit (%):	13
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

Unusual fire and explosion hazards:

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

7. HANDLING AND STORAGE

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Other Personal Protection Data:

Usual industrial work clothes. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	1000 ppm TWA 2400 mg/m ³ TWA		
PROPANE 74-98-6	15 - 20	1000 ppm TWA 1800 mg/m ³ TWA		
TOLUENE 108-88-3	1 - 5	200 ppm TWA	= 300 ppm Ceiling	
TITANIUM DIOXIDE 13463-67-7	1 - 5	15 mg/m ³ TWA dust total		

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	500 ppm TWA	750 ppm STEL		

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
PROPANE 74-98-6	15 - 20	1000 ppm TWA			
TOLUENE 108-88-3	1 - 5	20 ppm TWA			Can be absorbed through the skin.
TITANIUM DIOXIDE 13463-67-7	1 - 5	10 mg/m ³ TWA			

9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	Aerosol
pH:	not determined
Vapor pressure:	NOT DETERMINED mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	5.5
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	6.52
Specific Gravity:	.78
Evaporation rate (butyl acetate = 1.0):	5.6
Flash point (Fahrenheit):	-76
Flash point (Celsius):	-60
Lower explosive limit (%):	1
Upper explosive limit (%):	13
Autoignition temperature:	not determined

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Metal oxide fumes.

Sensitivity to static discharge: Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	= 5800 mg/kg Oral LD50 Rat
PROPANE 74-98-6	15 - 20	= 658 mg/L Inhalation LC50 Rat 4 h
NAPHTHA 64742-88-7	10 - 15	= 3000 mg/kg Dermal LD50 Rabbit > 5.28 mg/L Inhalation LC50 Rat 4 h > 5000 mg/kg Oral LD50 Rat
NAPHTHA 64742-89-8	5 - 10	= 3000 mg/kg Dermal LD50 Rabbit = 5000 mg/kg Oral LD50 Mouse

11. TOXICOLOGICAL INFORMATION

TOLUENE 108-88-3	1 - 5	= 12.5 mg/L Inhalation LC50 Rat 4 h = 12124 mg/kg Dermal LD50 Rat = 636 mg/kg Oral LD50 Rat = 8390 mg/kg Dermal LD50 Rabbit > 26700 ppm Inhalation LC50 Rat 1 h
TITANIUM DIOXIDE 13463-67-7	1 - 5	> 10000 mg/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

May cause birth defects. Female reproductive toxin.

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Developmental Toxicity	California Prop 65 - Reproductive (Male)
TOLUENE 108-88-3	1 - 5	Listed. initial date 1/1/91 - developmental toxicity	

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
TOLUENE 108-88-3	1 - 5	Listed. Initial date 8/1/09 - female reproductive toxicity	

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
TITANIUM DIOXIDE 13463-67-7	1 - 5			Monograph 47 [1989]

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
NAPHTHA 64742-88-7	10 - 15			male rat-some evidence; female rat-no evidence; male mice-no evidence; female mice-equivocal evidence
TOLUENE 108-88-3	1 - 5			male rat-no evidence; female rat-no evidence; male mice-no evidence; female mice-no evidence
TITANIUM DIOXIDE 13463-67-7	1 - 5			male rat-negative; female rat-negative; male mice-negative; female mice-negative

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	1 - 5	Present		

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

Canadian Transport of Dangerous Goods

Proper Shipping Name: CONSUMER COMMODITY ORM-D [Paint]
UN ID Number (msds): CONCOM

TDG Clear Language Exceptions:

For Dangerous Goods, the supplier may apply one of the following exceptions (TDG Reference): Limited quantity/Consumer Commodity (1.17), Does not sustain combustion, etc. (2.18), Viscous liquid (2.19), Flammable liquid General Exemption (1.33) or US DOT Reciprocity (9.1,3 & 4). Please consult current TDG regulations before applying any of these exceptions to subsequent shipments.

International Air Transport Association (IATA):

Proper Shipping Name: AEROSOLS, FLAMMABLE
Hazard Class: 2.1
UN ID Number (msds): UN1950

International Maritime Organization (IMO):

Proper Shipping Name: AEROSOLS, FLAMMABLE
Hazard Class: 2.1
IMO UN/ID Number (msds): UN1950

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS - Chemical Inventories

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada National Pollutant Release Inventory:

Ingredient Name CAS-No.	Approx. Weight %	NPRI Status
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	Part 4 Substance
PROPANE 74-98-6	15 - 20	Part 5 Substance
NAPHTHA 64742-88-7	10 - 15	Part 5 Substance
NAPHTHA 64742-89-8	5 - 10	Part 5 Substance

Ingredient Name CAS-No.	Approx. Weight %	NPRI Status
TOLUENE 108-88-3	1 - 5	Part 1, Group 1 Substance Part 5 Substance Part 1, Group 1 Substance

16. OTHER INFORMATION

HMIS Codes

Health: 2*
Flammability: 4
Reactivity: 1
PPE: X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By: Regulatory Affairs Department
 Print date: 06/Jan/2012
 Revision Date: 24/Dec/2011

Technical Information:

The Valspar Corporation
 PO Box 1461
 Minneapolis, MN 55440
 Tech Info Phone: 1-613-932-8960

24-Hour Medical Emergency Phone: 1-888-345-5732