

(11036)

SECTION 1

PRODUCT IDENTIFIER 4508.00100 TRUGLAZE EPXGL BASE 4508-010
XY-W

DATE OF PREPARATION NOVEMBER 30, 2012

PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,
STRONGSVILLE, OHIO 44136, U.S.A
AKZO NOBEL CANADA INC., 8200 KEELE STREET,
CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:
1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT
AKZO NOBEL PAINTS LLC

APPROVED MATERIAL

FEB 07 2013

MSDS # 11036

APPROVED BY *[Signature]***SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	WT. %:
CHEMICAL NAME BENZENE, ETHYL-	1-5
COMMON NAME : ETHYLBENZENE	
CAS NUMBER: 100-41-4	
CHEMICAL NAME 1,2,-ETHANEDIAMINE, N,N'-BIS(2-AMINOETHYL)-	.1-1.0
COMMON NAME : TRIETHYLENETETRAMINE	
CAS NUMBER: 112-24-3	
CHEMICAL NAME LIMESTONE	20-30
COMMON NAME : LIMESTONE	
CAS NUMBER: 1317-65-3	
CHEMICAL NAME BENZENE, DIMETHYL-	10-20
COMMON NAME : XYLENE	
CAS NUMBER: 1330-20-7	
CHEMICAL NAME TITANIUM OXIDE	10-20
COMMON NAME : TITANIUM DIOXIDE	
CAS NUMBER: 13463-67-7	
CHEMICAL NAME TALC	5-10
COMMON NAME : TALC	
CAS NUMBER: 14807-96-6	
CHEMICAL NAME QUARTZ	.1-1.0
COMMON NAME : QUARTZ	
CAS NUMBER: 14808-60-7	
CHEMICAL NAME 2-PROPANOL, 1-BUTOXY-	1-5
COMMON NAME : PROPYLENE GLYCOL NORMAL BUTYL ETHER	
CAS NUMBER: 5131-66-8	
CHEMICAL NAME 2-PROPANOL	5-10
COMMON NAME : ISOPROPYL ALCOHOL	
CAS NUMBER: 67-63-0	
CHEMICAL NAME FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH POLYETHYLENEPOLYAMINES	10-20
COMMON NAME : POLYAMIDE RESIN	
CAS NUMBER: 68410-23-1	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION

PROLONGED INHALATION MAY LEAD TO FATIGUE, DROWSINESS,
DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION,
NAUSEA, VOMITING, CHEST PAIN, BLURRED VISION, COUGHING,
DIFFICULTY WITH SPEECH, CENTRAL NERVOUS SYSTEM DEPRESSION,
INTOXICATION, TIGHTNESS OF CHEST, ANESTHETIC EFFECT OR
NARCOSIS, DIFFICULTY OF BREATHING, ALLERGIC RESPONSE,
TREMORS, LIVER DAMAGE, KIDNEY DAMAGE, LOSS OF CONSCIOUSNESS,
RESPIRATORY FAILURE, ASPHYXIATION, DEATH. POSSIBLE
SENSITIZATION TO RESPIRATORY TRACT.

SKIN CONTACT

IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE

DERMATITIS, DEFATTING, BLISTERING, SEVERE SKIN IRRITATION OR BURNS. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE DIZZINESS AND/OR LIGHTEADEDNESS, HEADACHE, NAUSEA, VOMITING, CENTRAL NERVOUS SYSTEM DEPRESSION.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION, SEVERE EYE IRRITATION OR BURNS, CORNEAL INJURY.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, DROWSINESS, DIZZINESS AND/OR LIGHTEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, BURNS OF THE MOUTH, THROAT, STOMACH, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, LOSS OF CONSCIOUSNESS.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
EYE, SKIN, RESPIRATORY DISORDERS, KIDNEY DISORDERS, LIVER DISORDERS, ALLERGIES.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.
DISPOSE OF CONTAMINATED LEATHER ITEMS, SUCH AS SHOES AND BELTS.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 70 F./ 21 C. LOWER EXPLOSIVE LIMIT 1.1 (%)
UPPER EXPLOSIVE LIMIT 7.0 (%)

FIRE EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES
WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE

PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.
 HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS
 CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN,
 ALDEHYDES.
 OXIDES OF CALCIUM, CYANIDES.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
 COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL
 REGULATIONS.
 ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.
 VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. SPILLS MAY
 BE COLLECTED WITH ABSORBENT MATERIALS. USE NON-SPARKING
 TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED
 MATERIAL IN PROPER CONTAINER. COMPLETE PERSONAL PROTECTIVE
 EQUIPMENT MUST BE USED DURING CLEANUP.
 LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND
 CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE
 ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE
 MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.
 SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE
 OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE
 STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.
 OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.
 KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND
 EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER
 HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
 KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.
 EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.
 GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION
 OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME :	ETHYLBENZENE				
CAS NUMBER:	100-41-4				
ACGIH (TWA) :	20	PPM	OSHA (TWA) :	100	PPM
ACGIH (STEL) :	125	PPM			
COMMON NAME :	LIMESTONE				
CAS NUMBER:	1317-65-3				
ACGIH (TWA) :	10	MG/M3	OSHA (TWA) :	5	MG/M3
COMMON NAME :	XYLENE				
CAS NUMBER:	1330-20-7				
ACGIH (TWA) :	100	PPM	OSHA (TWA) :	100	PPM
ACGIH (STEL) :	150	PPM			
COMMON NAME :	TITANIUM DIOXIDE				
CAS NUMBER:	13463-67-7				
ACGIH (TWA) :	10	MG/M3	OSHA (TWA) :	10	MG/M3
COMMON NAME :	TALC				
CAS NUMBER:	14807-96-6				
ACGIH (TWA) :	2	MG/M3	OSHA (TWA) :	.1	MG/M3
COMMON NAME :	QUARTZ				
CAS NUMBER:	14808-60-7				
ACGIH (TWA) :	.025	MG/M3	OSHA (TWA) :	0.1	MG/M3
COMMON NAME :	ISOPROPYL ALCOHOL				
CAS NUMBER:	67-63-0				
ACGIH (TWA) :	200	PPM	OSHA (TWA) :	400	PPM
ACGIH (STEL) :	400	PPM			

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE
 EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN

RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT
EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, APRON, BOOTS.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.426
BOILING RANGE (F/C):	180-293/ 82-145	WEIGHT PER GALLON:	11.88/ 14.27IMP
%VOLATILE BY VOLUME:	52.10		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES, ALDEHYDES, AMINES, AMMONIUM SALTS, NITRIC ACID, CAUSTICS.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO ACGIH YES A3

LD50: 3500.00 MG/KG ORL RAT

LD50: 15.35 GM/KG SKN RBT

LC50: 17.20 MG/L/4 HR IHL RAT

COMMON NAME : TRIETHYLENETETRAMINE

CAS NUMBER: 112-24-3

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 2500.00 MG/KG ORL RAT

LD50: 1600.00 MG/KG ORL MOU

LD50: 805.00 MG/KG SKN RBT

COMMON NAME : LIMESTONE

CAS NUMBER: 1317-65-3

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 6450.00 MG/KG ORL RAT

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:>1700.00 MG/KG SKN RBT

LD50: 4300.00 MG/KG ORL RAT

LC50: 5000.00 PPM/4HR IHL RAT

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

CARCINOGENICITY LISTED BY: NTP YES 2B IARC YES 2B OSHA NO ACGIH NO

LD50: 24.00 GM/KG ORL RAT

LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : TALC

4508.00100 TRUGLAZE EPXGL BASE 4508-010

CAS NUMBER: 14807-96-6
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH YES A4
 COMMON NAME : QUARTZ
 CAS NUMBER: 14808-60-7
 CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA NO ACGIH YES A2
 COMMON NAME : PROPYLENE GLYCOL NORMAL BUTYL ETHER
 CAS NUMBER: 5131-66-8
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 3100.00 MG/KG SKN RBT
 LD50: 5.66 ML/KG ORL RAT
 COMMON NAME : ISOPROPYL ALCOHOL
 CAS NUMBER: 67-63-0
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO A4
 LD50: 5045.00 MG/KG ORL RAT
 LD50: 12.80 GM/KG SKN RBT
 COMMON NAME : POLYAMIDE RESIN
 CAS NUMBER: 68410-23-1
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50:>5000.00 MG/KG SKN RAT
 LD50: 800.00 MG/KG ORL RBT
 LD50:>5000.00 MG/KG ORL RAT

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT IS MODERATELY TOXIC BY INGESTION.
 CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.
 NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
 OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN
 AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
 DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS
 MAY BE HARMFUL OR FATAL.
 OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER,
 KIDNEY, CENTRAL NERVOUS SYSTEM, BLOOD.
 CARCINOGENICITY INHALATION OF NON-ASBESTIFORM COSMETIC GRADE TALC FOR
 2 YEARS AT 6 AND 18 MG/M3 PRODUCED CLEAR EVIDENCE OF
 CARCINOGENICITY IN FEMALE RATS (LUNG AND ADRENAL TUMORS) AND
 SOME EVIDENCE OF CARCINOGENICITY IN MALE RATS (ADRENAL
 TUMORS). NO EVIDENCE OF CARCINOGENICITY WAS DEMONSTRATED IN
 MALE AND FEMALE MICE EXPOSED UNDER THE SAME CONDITIONS.
 MICROSCOPIC EXAMINATION OF THE LUNGS OF RATS AND MICE
 EXPOSED TO TALC REVEALED ADDITIONAL EXPOSURE RELATED EFFECTS
 PRIMARILY ASSOCIATED WITH THE INFLAMMATORY RESPONSE.
 CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY
 INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS
 CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO
 A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.
 THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED
 CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.
 THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS
 EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN
 CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR
 CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE
 EVIDENCE FOR CANCER IN EXPOSED HUMANS.
 IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL
 TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM
 PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG
 AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES
 SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE
 RESULTS TO HUMANS IS NOT KNOWN.
 THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC)
 HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC
 TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF
 CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF
 CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

CARCINOGENICITY

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED INHALED TALC NOT CONTAINING ASBESTOS OR ASBESTIFORM FIBRES AS NOT CLASSIFIABLE TO ITS CARCINOGENICITY (GROUP 3). PERINEAL USE OF TALC-BASED BODY POWDER IS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B).

REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

POSSIBLE REPRODUCTIVE HAZARD BASED ON ANIMAL DATA.

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT UN1263, PAINT, 3, PGII
 IMDG UN1263, PAINT, 3, PGII, LIMITED QUANTITY
 UN1263, PAINT, CLASS 3, PGII
 IATA NOT AVAILABLE
 TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

		SARA	SARA	CERCLA	HAZ AIR	MARINE
		302	313	302.4	POLLUTANT	POLTNT
CAS NUMBER:	100-41-4	NO	YES	YES	YES	NO
COMMON NAME :	ETHYLBENZENE					
CAS NUMBER:	1330-20-7	NO	YES	YES	YES	NO
COMMON NAME :	XYLENE					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.