4308-0400H

PAGE: 1

10-20

SECTION 1 DEVGUARD 4308H DEEP TINT BASE PRODUCT IDENTIFIER 4308-0400H DATE OF PREPARATION NOVEMBER 6, 2012 APPROVED MATERIAL PRODUCT USE PROTECTIVE COATING MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD, STRONGSVILLE, OHIO 44136, U.S.A JAN 2 7 2014 AKZO NOBEL CANADA INC., 8200 KEELE STREET, CONCORD, ONTARIO L4K 2A5, CANADA. MSDS # 11054 EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643 PPROVED BYO MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT AKZO NOBEL PAINTS LLC SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS WT.8: INGREDIENT CHEMICAL NAME ALKYD RESIN 1 - 5COMMON NAME : ALKYD RESIN CAS NUMBER: CONFIDENTIAL CHEMICAL NAME 1-HYDROXYETHYL-1-2-ALKENYLIMIDAZOLINE 1 - 5HMIRC #4984 EXEMPTION GRANTED 01/31/2005 COMMON NAME: HIGH MOLECULAR WEIGHT ALKYLOLAMINO AMIDE CAS NUMBER: CONFIDENTIAL CHEMICAL NAME ALKYD RESIN 1 - 5COMMON NAME : ALKYD RESIN CAS NUMBER: CONFIDENTIAL 20-30 CHEMICAL NAME LONG OIL ALKYD RESIN COMMON NAME : LONG OIL ALKYD RESIN CAS NUMBER: CONFIDENTIAL CHEMICAL NAME MEDIUM OIL ALKYD RESIN 10-20 COMMON NAME : MEDIUM OIL ALKYD RESIN CAS NUMBER: CONFIDENTIAL CHEMICAL NAME BENZENE, ETHYL-.1-1.0 COMMON NAME : ETHYLBENZENE 100-41-4 CAS NUMBER: CHEMICAL NAME 2-HEPTANONE 1 - 5COMMON NAME: METHYL AMYL KETONE CAS NUMBER: 110-43-0 CHEMICAL NAME BENZENE, DIMETHYL-.1-1.0COMMON NAME : XYLENE CAS NUMBER: 1330-20-7 CHEMICAL NAME KAOLIN 1 - 5COMMON NAME : CLAY 1332-58-7 CAS NUMBER: 1-5 CHEMICAL NAME TITANIUM OXIDE COMMON NAME: TITANIUM DIOXIDE CAS NUMBER: 13463-67-7 1-5 CHEMICAL NAME HEXANOIC ACID, 2-ETHYL-, ZIRCONIUM SALT COMMON NAME : ZIRCONIUM CARBOXYLATE 22464-99-9 CAS NUMBER: CHEMICAL NAME NEODECANOIC ACID, COBALT SALT -1-1.0COMMON NAME : COBALT NEODECANOATE 27253-31-2 CAS NUMBER: CHEMICAL NAME ACETIC ACID, 1,1-DIMETHYLETHYL ESTER 10 - 20TERT-BUTYL ACETATE COMMON NAME : CAS NUMBER: 540-88-5

CHEMICAL NAME SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC

4308-0400H PAGE: 2

COMMON NAME: MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS NUMBER: 64742-88-7

CHEMICAL NAME QUATERNARY AMMONIUM COMPOUNDS, BIS(HYDROGENATED 1-5

TALLOW ALKYL) DI=METHYL, SALTS WITH BENTONITE

COMMON NAME : DISPERSANT, ORGANOCLAY

CAS NUMBER: 68953-58-2

CHEMICAL NAME STODDARD SOLVENT 10-20

COMMON NAME: MINERAL SPIRITS

CAS NUMBER: 8052-41-3

CHEMICAL NAME BENZENE, 1-CHLORO-4-(TRIFLUOROMETHYL) 1-5

COMMON NAME : PARACHLOROBENZOTRIFLUORIDE

CAS NUMBER: 98-56-6

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS

MEMBRANE IRRITATION, DROWSINESS, DIZZINESS AND/OR

LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, COUGHING, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING,

ALLERGIC RESPONSE, BLOOD ABNORMALITIES, SEVERE LUNG IRRITATION OR DAMAGE, LIVER DAMAGE, KIDNEY DAMAGE, CONVULSIONS, PNEUMOCONIOSIS, LOSS OF CONSCIOUSNESS,

ASPHYXIATION. POSSIBLE SENSITIZATION TO RESPIRATORY TRACT.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE

DERMATITIS, DEFATTING, ALLERGIC RESPONSE, SEVERE SKIN IRRITATION OR BURNS. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE

CENTRAL NERVOUS SYSTEM DEPRESSION.

EYE CONTACT IRRITATION OF EYES, THIS MATERIAL IS CORROSIVE AND MAY

CAUSE BURNS ON CONTACT. PROLONGED OR REPEATED CONTACT CAN

CAUSE CONJUNCTIVITIS, REDNESS OF EYES, SEVERE EYE

IRRITATION OR BURNS.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO

ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, MUCOUS MEMBRANE IRRITATION, HEADACHE,

UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA,

GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, BLOOD ABNORMALITIES, LIVER DAMAGE,

KIDNEY DAMAGE, CONVULSIONS, LOSS OF CONSCIOUSNESS.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS, KIDNEY DISORDERS, LIVER DISORDERS, NERVOUS SYSTEM DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED

BREATHING.

GET EMERGENCY MEDICAL ATTENTION.

HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL

HELP FOR ANY BREATHING DIFFICULTY.

REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING,

HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS,

GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL

4308-0400H

PAGE: 3

(%)

ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.

WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT

FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION

IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA)

68 F./ 20 C. LOWER EXPLOSIVE LIMIT .7

UPPER EXPLOSIVE LIMIT 8.9 (%)

FIRE EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

WATER FOG.

CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.

VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED

TEMPERATURES.

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, AMMONIA, TOXIC GASES.

HALOGENATED COMPOUNDS.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.
VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. USE
NON-SPARKING TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL.

PLACE COLLECTED MATERIAL IN PROPER CONTAINER.

AVOID WETTING SPILLS AS SURFACES CAN BECOME VERY SLIPPERY. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING, CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES. SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

## HANDLING AND STORAGE

STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

KEEP AWAY FROM DIRECT SUNLIGHT, HEAT AND ALL SOURCES OF IGNITION.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION

OF STATIC CHARGE.
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : ETHYLBENZENE CAS NUMBER: 100-41-4

ACGIH(TWA): 20 PPM OSHA(TWA): 100 PPM ACGIH(STEL): 125 PPM

COMMON NAME : METHYL AMYL KETONE

CAS NUMBER: . 110-43-0

ACGIH(TWA): 50 PPM OSHA(TWA): 100 PPM

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7
ACGIH(TWA): 100 PPM OSHA(TWA): 100 PPM

ACGIH(STEL): 150 PPM

COMMON NAME : CLAY

CAS NUMBER: 1332-58-7

ACGIH(TWA): 2 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

ACGIH(TWA): 10 MG/M3 OSHA(TWA): 10 MG/M3

COMMON NAME : ZIRCONIUM CARBOXYLATE

CAS NUMBER: 22464-99-9

ACGIH(TWA): 5 MG/M3 OSHA(TWA): 5 MG/M3

ACGIH(STEL): 10 MG/M3

COMMON NAME : TERT-BUTYL ACETATE

CAS NUMBER: 540-88-5

ACGIH(TWA): 200 PPM OSHA(TWA): 200 PPM

COMMON NAME : MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS NUMBER: 64742-88-7

ACGIH(TWA): 100 PPM OSHA(TWA): 500 X PPM

COMMON NAME : DISPERSANT, ORGANOCLAY

CAS NUMBER: 68953-58-2

ACGIH(TWA): 10 MG/M3 OSHA(TWA): 15 MG/M3

COMMON NAME : MINERAL SPIRITS

CAS NUMBER: 8052-41-3

ACGIH(TWA): 100 PPM OSHA(TWA): 500 PPM

X AS PETROLEUM DISTILLATES

## RESPIRATORY PROTECTION

THE SUPPLIER OF PARACHLOROBENZOTRIFLUORIDE (PCBTF) HAS ESTABLISHED AN OCCUPATIONAL EXPOSURE LIMIT FOR PCBTF OF 25 PPM AS AN 8-HOUR TWA. WHEN AIRBORNE CONCENTRATIONS OF PCBTF ARE UNKNOWN OR EXCEED ESTABLISHED GUIDELINES, RESPIRATORY PROTECTION IS REQUIRED.

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN

EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC

SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT

29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT

BUILD-UP OF VAPORS.

USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.

IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, FACE SHIELD, APRON.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:

NOT AVAILABLE SPECIFIC GRAVITY:

208-417/ 98-214 WEIGHT PER GALLON:

1.002 8.35/ 10.03IMP

BOILING RANGE (F/C): %VOLATILE BY VOLUME:

52.13

WHITE

PHYSICAL STATE:

LIQUID

APPEARANCE

NOT AVAILABLE

SOLUBILITY IN WATER: NOT AVAILABLE PH:

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, REDUCING AGENTS, BASES, METAL SALTS, COMBUSTIBLE MATERIALS.

NITRATES, STYRENE MONOMER.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : HIGH MOLECULAR WEIGHT ALKYLOLAMINO AMIDE

CAS NUMBER: CONFIDENTIAL

ACGIH NO CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO

LD50:>2000.00 MG/KG ORL RAT

COMMON NAME : ALKYD RESIN

CONFIDENTIAL CAS NUMBER:

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

ACGIH YES A3 CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO

LD50: 3500.00 MG/KG ORL RAT

SKN RBT LD50: 15.35 GM/KG

LC50: 17.20 MG/L/4 HR IHL RAT

COMMON NAME : METHYL AMYL KETONE

CAS NUMBER: 110-43-0

IARC NO CARCINOGENICITY LISTED BY: NTP NO OSHA NO ACGIH NO

LD50: 12.60 ML/KG SKN RBT

LD50: 1670.00 MG/KG ORL RAT

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:>1700.00 MG/KG SKN RBT

LD50: 4300.00 MG/KG ORL RAT

PAGE: 6

LC50: 5000.00 PPM/4HR IHL RAT COMMON NAME: CLAY							
CAS NUMBER: 1332-58-7		-					
CARCINOGENICITY LISTED BY: NTP NO	IARC	NO		OSHA	NO	ACGIH	NO
COMMON NAME: TITANIUM DIOXIDE							
CAS NUMBER: 13463-67-7							
CARCINOGENICITY LISTED BY: NTP YES 2B	IARC	YES	2B	OSHA	NO	ACGIH	NO
LD50: 24.00 GM/KG ORL RAT							
LC50: 6820.00 MG/M3/4HR IHL RAT							
COMMON NAME : ZIRCONIUM CARBOXYLATE							
CAS NUMBER: 22464-99-9							
CARCINOGENICITY LISTED BY: NTP NO	IARC	NO		OSHA	NO	ACGIH	NO
COMMON NAME : COBALT NEODECANOATE							
CAS NUMBER: 27253-31-2							
CARCINOGENICITY LISTED BY: NTP NO	IARC	YES	2B	OSHA	ИО	ACGIH	ИО
COMMON NAME : TERT-BUTYL ACETATE							
CAS NUMBER: 540-88-5							
CARCINOGENICITY LISTED BY: NTP NO	IARC	NO		OSHA	NO	ACGIH	NO
LD50: 4100.00 MG/KG ORL RAT							
LD50:> 2.00 GM/KG SKN RBT							
LC50:>2230.00 MG/M3/4HR IHL RAT							
COMMON NAME : MEDIUM ALIPHATIC SOLVENT	NAPH	ITHA					
CAS NUMBER: 64742-88-7							
CARCINOGENICITY LISTED BY: NTP NO	IARC	ИО		OSHA	NO	ACGIH	NO
LD50: 28.00 GM/KG SKN RBT							
LD50: 28.00 GM/KG ORL RAT							
COMMON NAME : DISPERSANT, ORGANOCLAY							
CAS NUMBER: 68953-58-2							***
CARCINOGENICITY LISTED BY: NTP NO	IARC	NO		OSHA	NO	ACGIH	NO
COMMON NAME : MINERAL SPIRITS							
CAS NUMBER: 8052-41-3	****	370		00117	NO	* **	NΟ
CARCINOGENICITY LISTED BY: NTP NO	LARC	NO		OSHA	NO	ACGIH	NO
LD50:> 3.00 GM/KG SKN RBT							
LD50:> 5.00 GM/KG ORL RAT							
COMMON NAME : PARACHLOROBENZOTRIFLUORI	.DE						
CAS NUMBER: 98-56-6 CARCINOGENICITY LISTED BY: NTP NO	T 70 70 CT	NO		ЛСПЛ	NIO	ACCTU	NΟ
	TARC	NO		OSBA	140	ACGIII	140
LD50:> 6.80 GM/KG ORL RAT							
LD50:> 2.70 GM/KG SKN RBT LC50: 4479.00 PPM IHL RAT							
SUPPLEMENTAL HEALTH INFORMATION							
THIS MATERIAL IS COR	RROST	7F.: 7	AVOTI	р сои	TACT.		

THIS MATERIAL IS CORROSIVE; AVOID CONTACT.

NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED

OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN

AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY

DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS

MAY BE HARMFUL OR FATAL.

A 28-DAY INHALATION STUDY WAS CONDUCTED WITH PCBTF AT DOSE

LEVELS OF 100, 250, 500, AND 1000 PPM IN RATS FOR 6 HR/DAY,

5 DAYS/WEEK. CLINICAL SIGNS INCLUDED INCREASED ACTIVITY AT

250 PPM AND ABOVE. HEPATOCYTE HYPERTROPHY WAS OBSERVED IN

ALL ANIMALS AT DOSE LEVELS OF 500 AND 1000 PPM AND SOME

ANIMALS AT LOWER LEVELS. KIDNEY/BODY WEIGHT RATIOS WERE

SIGNIFICANTLY INCREASED IN MALE AND FEMALE RATS. MALE KIDNEY CHANGES WERE ATTRIBUTED TO ALPHA-2U-GLOBULIN AND THEREFORE

NOT RELEVANT TO HUMANS.

GAVAGE STUDIES OF PCBTF IN LABORATORY RODENTS FOR TREATMENT PERIODS OF 14, 28, AND 90 DAYS HAVE DEMONSTRATED SIGNIFICANT LIVER AND KIDNEY TOXICITY AT DOSE LEVELS OF 400-1000 MG/KG/DAY. EVIDENCE OF TARGET ORGAN TOXICITY INCLUDED SIGNIFICANT INCREASES IN RELATIVE LIVER AND KIDNEY WEIGHTS, CLINICAL CHEMISTRY VALUES AND HISTOPATHOLOGICAL FINDINGS. RENAL TOXICITY WHICH OCCURRED ONLY IN MALE RATS, WAS ATTRIBUTED TO HYALINE DROPLET NEPHROPATHY AND IS HIGHLY UNLIKELY TO DEVELOP IN HUMANS. THE NOAEL'S FOR ALL THESE STUDIES RANGE FROM 10 TO 100 MG/KG/DAY.

A 90 DAY RAT INHALATION TOXICITY AND NEUROBEHAVIORAL STUDY WAS CONDUCTED USING EXPOSURES OF 0-250 PPM FOR 6 HRS/DAY, 5 DAYS/WEEK. NO PCBTF-RELATED MACROSCOPIC OBSERVATIONS. PCBTF-RELATED CENTRILOBULAR HYPERTROPHY WAS PRESENT IN THE LIVERS OF MALES AND FEMALES AT THE HIGHEST DOSE AFTER 13 WEEKS. NO CENTRILOBULAR HYPERTROPHY WAS OBSERVED AT ANY LEVEL AMONG RECOVERY ANIMALS. THERE WERE NO PCBTF-RELATED EFFECTS ON THE NERVOUS SYSTEM AS MEASURED BY A FUNCTIONAL OBSERVATION BATTERY, MUSCULAR ACTIVITY MEASUREMENTS AND NEUROPATHOLOGY. A NOEL OF 50 PPM WAS ESTABLISHED IN THIS STUDY FOR LIVER HEPATOCYTE HYPERTROPHY IN MALE AND FEMALE RATS. IF THE HEPATOCYTE HYPERTROPHY OBSERVED IS CONSIDERED TO BE AN ADAPTIVE RESPONSE TO PCBTF, THE NOAEL FOR THIS STUDY IS 250 PPM.

OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER, KIDNEY, CENTRAL NERVOUS SYSTEM, BLOOD.

CARCINOGENICITY

STODDARD SOLVENT IIC HAS BEEN SHOWN TO CAUSE KIDNEY TUMORS IN MALE RATS IN A NATIONAL TOXICOLOGY PROGRAM (NTP) STUDY. THESE TUMORS WERE ASSOCIATED WITH A SPECIFIC PROTEIN, ALPHA-2U-MICROGLOBULIN. BECAUSE HUMANS DO NOT PRODUCE THIS PROTEIN STODDARD SOLVENT IIC HAS NOT BEEN CLASSIFIED AS A HUMAN CARCINOGEN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE EVIDENCE FOR CANCER IN EXPOSED HUMANS.

IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED COBALT AND CERTAIN COBALT COMPOUNDS AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B). INJECTION OF METALLIC COBALT, COBALT ALLOYS, AND CERTAIN COBALT COMPOUNDS HAS RESULTED IN THE DEVELOPMENT OF LOCALIZED TUMORS IN LABORATORY ANIMALS.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

CONTAINS METHYL ETHYL KETOXIME (MEKO). IN A LIFETIME, INHALATION STUDY, LIVER CARCINOMAS WERE OBSERVED IN RODENTS EXPOSED TO MEKO. THE RELEVANCE TO HUMANS IS UNKNOWN.

## REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

MUTAGENICITY

CONTAINS PARACHLOROBENZOTRIFLUORIDE (PCBTF). THE AMES TEST WAS NEGATIVE WITH AND WITHOUT S9 METABOLIC ACTIVATION. PCBTF INDUCED SISTER-CHROMATID-EXCHANGES (SCES) IN MOUSE LYMPHOMA CELLS WITH AND WITHOUT S9 METABOLIC ACTIVATION AT DOSES FROM 2.5 TO 40 MICROGRAMS PER MILLILITER. IN THE MOUSE LYMPHOMA ASSAY WHICH DID NOT INCORPORATE METABOLIC ACTIVATION, A DOSE-RESPONSE EFFECT WAS OBSERVED.

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC

ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

AVOID DISCHARGE TO NATURAL WATERS. SECTION 14: TRANSPORT INFORMATION

DOT UN1263, PAINT, 3, PGII

IMDG NOT AVAILABLE
IATA NOT AVAILABLE
TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

YES YES

SARA SARA CERCLA HAZ AIR MARINE 302 313 302.4 POLLUTANT POLTNT

YES

NO

CAS NUMBER: 100-41-4

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 1330-20-7 NO YES YES YES NO

NO

COMMON NAME : XYLENE

CAS NUMBER: 27253-31-2 NO YES NO YES NO

COMMON NAME : COBALT NEODECANOATE

CAS NUMBER: 540-88-5 NO NO YES NO NO

COMMON NAME : TERT-BUTYL ACETATE

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE

4308-0400H PAGE: 9

HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.

 $(x_1,\dots,x_n) \mapsto (x_1,\dots,x_n) = x_1$