

(11059)

M A T E R I A L S A F E T Y D A T A S H E E T

EE-2020 EPOXY HARDNER COMP B

Page: 1
2/15/2012

PRODUCT NAME: EE-2020 EPOXY HARDNER COMP B
PRODUCT CLASS: CATALYST
PRODUCT CODE: C86-0131

H M I S C O D E S : H F R P
2 3 2 X

=====SECTION I - MANUFACTURER IDENTIFICATION=====

MANUFACTURER'S NAME: STRATHMORE PRODUCTS, INC.
ADDRESS 1970 WEST FAYETTE STREET
P.O. BOX 151
SYRACUSE, NY 13201

EMERGENCY PHONE DAY: 315-488-5401

NIGHT: FOR HEALTH - POISON CONTROL CENTER: 315/476-4766

FOR SPILLS - CHEMTEL: 1-800/255-3924

DATE OF PREPARATION: 2/15/2012

TIME OF PREPARATION: 16:05:46

REVISION DATE: 02/03/11

=====SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		RANGE
		mm Hg @ TEMP		PERCENT
+ CALCIUM CARBONATE ACGIH TLV: 10.0 MG/M3 OSHA PEL: 15.0 MG/M3	1317-65-3			
ISOPROPYL ALCOHOL ACGIH TLV: 200 PPM OSHA PEL: 400 PPM	67-63-0	33	68	10-20%
- ACGIH TLV & OSHA PEL: NOT ESTABLISHED				
AROMATIC #100 ACGIH TLV & OSHA PEL: NOT ESTABLISHED EXXON RECOMMENDATION: 50 PPM	64742-95-6	1.0		0-2%
* BUTYL ALCOHOL ACGIH TLV: 20 PPM OSHA PEL: 100 PPM	71-36-3	4.0	68	0-2%
* XYLENE ACGIH TLV: 100.0 PPM OSHA PEL: 100.0 PPM	1330-20-7	9.5		0-2%
ETHYLBENZENE ACGIH TLV: 100 PPM OSHA PEL: 100 PPM	100-41-4	7.1	68	0-1%

SARA 313 INFORMATION:

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

+ Indicates component(s) considered nuisance dust(s) in their dry form.

FOOTNOTE:

*N/A

APPROVED MATERIAL

 MAR 05 2012

 MSDS # 11059
 APPROVED BY [Signature]

=====SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS=====

BOILING RANGE OF SEC. II: 180°F - 306°F WEIGHT per GALLON: 9.77 lb/gl

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

% SOLIDS BY VOLUME: 72.04

V.O.C.: 1.87 lb/gl

=====SECTION IV - FIRE AND EXPLOSION HAZARD DATA=====

M A T E R I A L S A F E T Y D A T A S H E E T

EE-2020 EPOXY HARDNER COMP B

Page: 3
2/15/2012

DAMAGE.

NOTE: A CASE EFFECT SHOWED ACTIVE LIVER & KIDNEY DYSFUNCTION AT EXTREMELY HIGH LEVELS OF EXPOSURE TO XYLENE AND TOLUENE.

NOTE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

CARCINOGENICITY:

THIS PRODUCT CONTAINS ETHYLBENZENE AND/OR NAPHTHALENE, CLASSIFIED BY IARC AS A GROUP 2B CARCINOGEN - POSSIBLY CARCINOGENIC TO HUMANS. THERE IS INADEQUATE EVIDENCE IN HUMANS BUT SUFFICIENT EVIDENCE IN EXPERIMENTAL ANIMALS FOR THE CARCINOGENICITY OF ETHYLBENZENE AND/OR NAPHTHALENE.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, GIVE MOUTH-TO-MOUTH RESUSCITATION AND KEEP WARM AND QUIET. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL HELP IMMEDIATELY. SPLASH (EYES): FLUSH IMMEDIATELY WITH COPIOUS QUANTITIES OF WATER FOR 15 MINUTES AND TAKE TO A PHYSICIAN FOR DEFINITIVE MEDICAL TREATMENT. SPLASH (SKIN): REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE A PHYSICIAN.

IF SWALLOWED, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY AND GET MEDICAL HELP. DO NOT INDUCE VOMITING UNLESS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

EXPOSURE MAY AGGRAVATE PRE-EXISTING SKIN, EYE AND RESPIRATORY DISORDERS.

=====**SECTION VI - REACTIVITY DATA**=====

STABILITY:

STABLE

CONDITIONS TO AVOID:

EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, ACIDS, BASES, AMINE COMPOUNDS, AND AVOID CONTAMINATION WITH COMPONENT I, COMPONENT A OR PART A.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

DECOMPOSITION MAY PRODUCE SMOKE, ACRID FUMES, CARBON DIOXIDE AND/OR CARBON MONOXIDE, AND POSSIBLY OTHER TOXIC VAPORS.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

=====**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTION SPARKS). AVOID BREATHING VAPORS. WEAR APPROPRIATE PROTECTIVE EQUIPMENT. VENTILATE AREA. ADD INERT ABSORBENT AND REMOVE TO APPROPRIATE CONTAINER FOR DISPOSAL WITH NON-SPARKING TOOLS. KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATER AND SOIL.

WASTE DISPOSAL METHOD:

M A T E R I A L S A F E T Y D A T A S H E E T

EE-2020 EPOXY HARDNER COMP B

Page: 4
2/15/2012

DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

=====**SECTION VIII - CONTROL MEASURES**=====

RESPIRATORY PROTECTION:

IF USE CONDITIONS OF THIS PRODUCT GENERATE VAPORS OR MISTS, OR IF THE TLV'S SHOWN IN SECTION II ARE EXCEEDED, A NIOSH APPROVED RESPIRATOR DESIGNED TO REMOVE ORGANIC VAPORS SHOULD BE WORN. IN CONFINED AREAS, USE A NIOSH APPROVED AIRLINE TYPE RESPIRATOR OR HOOD.

VENTILATION:

PROVIDE ADEQUATE VENTILATION TO KEEP TLV OF MOST HAZARDOUS INGREDIENT IN SECTION II BELOW ACCEPTABLE LEVEL, AND TO KEEP LEL IN SECTION IV BELOW STATED LIMIT.

PROTECTIVE GLOVES:

SOLVENT RESISTANT GLOVES ARE REQUIRED FOR PROLONGED OR REPEATED CONTACT WITH LIQUID.

EYE PROTECTION:

IF A SPLASHING HAZARD EXISTS OR IF THERE IS POTENTIAL EYE CONTACT, WEAR SAFETY EYEWEAR SUCH AS CHEMICAL GOGGLES OR FACE SHIELDS TO PREVENT CONTACT OF LIQUID WITH EYES. EYE FLUSHING EQUIPMENT SHOULD BE IMMEDIATELY AVAILABLE.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR APPROPRIATE PROTECTIVE OUTERWEAR TO PROTECT AGAINST CLOTHING CONTAMINATION AND PROLONGED SKIN CONTACT. WHEN NECESSARY, WEAR CHEMICAL AND/OR SOLVENT RESISTANT BOOTS TO PROTECT FEET AND SHOES FROM CONTAMINATION. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES THAT CANNOT BE THOROUGHLY CLEANED BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING RESTROOM.

=====**SECTION IX - SPECIAL PRECAUTIONS**=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

DO NOT STORE ABOVE 120 DEG F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR OPEN FLAME. KEEP CONTAINERS TIGHTLY COVERED AND UPRIGHT TO PREVENT LEAKAGE. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS:

WARNING - FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. VAPORS MAY CAUSE FLASH FIRE. WHEN POURING/TRANSFERRING THIS MATERIAL TO ANOTHER CONTAINER OR EQUIPMENT, GROUND ALL CONTAINERS AND EQUIPMENT AS STATIC ELECTRICITY MAY IGNITE VAPORS. VAPORS HARMFUL. MAY CAUSE IRRITATION TO EYES, NOSE, THROAT, SKIN AND RESPIRATORY TRACT. PROLONGED OR REPEATED CONTACT OF LIQUID OR BREATHING OF VAPORS OR MISTS MAY CAUSE DELAYED AND SERIOUS INJURY. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS OR SPRAY MIST. AVOID CONTACT WITH EYES AND SKIN. DO NOT TAKE INTERNALLY.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS MAY BE HARMFUL OR FATAL.

SPECIAL PRECAUTIONS:

IN USE, THIS PRODUCT MUST BE BLENDED WITH COMPONENT I, COMPONENT A OR PART A, AND IT WILL HAVE THE HAZARDS OF BOTH COMPONENTS. BEFORE USING, CHECK THE MSDS FOR COMP. I, COMP. A OR PART A AND FOLLOW ALL PRECAUTIONS.

M A T E R I A L S A F E T Y D A T A S H E E T

EE-2020 EPOXY HARDNER COMP B

Page: 5
2/15/2012

MISCELLANEOUS PRECAUTIONS:

WARNING - EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

=====SECTION X - DISCLAIMER=====

SARA 313 INFORMATION:

*N/A

FOOTNOTE:

USER'S RESPONSIBILITY: THE RESPONSIBILITY TO PROVIDE A SAFE WORKPLACE REMAINS WITH THE USER. THE USER SHOULD CONSIDER THE HEALTH HAZARDS AND SAFETY INFORMATION CONTAINED HEREIN AS A GUIDE AND SHOULD TAKE THOSE PRECAUTIONS REQUIRED IN AN INDIVIDUAL OPERATION TO INSTRUCT EMPLOYEES AND DEVELOP WORK PRACTICE PROCEDURES FOR A SAFE WORK ENVIRONMENT. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, STRATHMORE PRODUCTS, INC., ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY, RELIABILITY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH AND SAFETY HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.