



**BUTYL BRICK RED - 30 CTG**

Version 3.  
REVISION DATE: 12/20/2011

Print Date 06/11/2012

**SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**

Product Information

Trade name : BUTYL BRICK RED - 30 CTG  
Product code : S30817 323

Supplier : Tremco Canada division  
220 Wicksteed Avenue  
Toronto, ON M4H 1G7

Telephone : (416) 421-3300  
Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation Information

Prepared by: : Sewnauth Raghunandan  
Date: : 12/20/2011  
Telephone : (416) 421-3300

**APPROVED MATERIAL**  
  
JUL 13 2012  
  
MSDS # 11065  
APPROVED BY *[Signature]*

**SECTION 2 - HAZARDS IDENTIFICATION**

Emergency Overview

Rust Red. Non-sag gunnable paste. No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

- Inhalation : No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract.
- Eyes : Slightly irritating.
- Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
- Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause

**BUTYL BRICK RED - 30 CTG**

Version 3.

Print Date 06/11/2012

REVISION DATE: 12/20/2011

defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**SECTION 3 : HAZARDOUS INGREDIENTS**

Chemical Name	CAS-No.	Weight % Range
Stoddard solvent (Mineral Spirits)	8052-41-3	10.0 - 30.0
Talc	14807-96-6	5.0 - 10.0
Xylene	1330-20-7	1.0 - 5.0
Iron oxide	1309-37-1	1.0 - 5.0
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0
Ethylbenzene	100-41-4	0.1 - 1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5: FIRE / EXPLOSION HAZARDS**

Flash point	:	Not available.
Method	:	Not available.
Lower explosion limit	:	1.00 %(V) Solvent
Upper explosion limit	:	5 %(V) Solvent
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

**SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

**BUTYL BRICK RED - 30 CTG**

Version 3.

Print Date 06/11/2012

REVISION DATE: 12/20/2011

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Do not use in confined or poorly ventilated areas. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION****Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Stoddard solvent (Mineral Spirits)	8052-41-3	Ontario TWAEV: ACGIH TWA:	525 mg/m <sup>3</sup> 100 ppm	
Talc	14807-96-6	Ontario TWAEV: ACGIH TWA: Ontario TWAEV:	2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 2 ppm	Respirable. Respirable fraction.
Xylene	1330-20-7	Ontario TWAEV: Ontario STEV: ACGIH TWA: ACGIH STEL:	435 mg/m <sup>3</sup> 650 mg/m <sup>3</sup> 100 ppm 150 ppm	
Iron oxide	1309-37-1	Ontario TWAEV: ACGIH TWA: Ontario TWAEV: ACGIH TWA:	5 mg/m <sup>3</sup> 5 mg/m <sup>3</sup> 5 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Dust and fume.as Fe Respirable fraction. Respirable. Respirable fraction.
1,2,4-Trimethylbenzene	95-63-6	Ontario TWAEV: ACGIH TWA:	123 mg/m <sup>3</sup> 25 ppm	
Ethylbenzene	100-41-4	Ontario TWAEV: Ontario STEV: ACGIH TWA: ACGIH STEL:	435 mg/m <sup>3</sup> 540 mg/m <sup>3</sup> 100 ppm 125 ppm	

**BUTYL BRICK RED - 30 CTG**

Version 3.

Print Date 08/11/2012

REVISION DATE: 12/20/2011

Chemical Name	CAS Number	Regulation	Limit	Form
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	Ontario TWAEV:	0.10 mg/m <sup>3</sup>	Respirable fraction.
		ACGIH TWA:	0.025 mg/m <sup>3</sup>	Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Physical State	: Paste
Form	: Non-sag gunnable paste
Color	: Rust Red
Odor	: Naptha
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 400 °C, 752 °F
Water solubility	: Negligible
Evaporation Rate:	: Not available.
Specific Gravity	: 1.391
% Volatile Weight	: 15 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Oxidizing agents.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg ( Rabbit )



**BUTYL BRICK RED - 30 CTG**

Version 3.  
REVISION DATE: 12/20/2011

Print Date 06/11/2012

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

TDG / DOT Shipping Description:  
NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**Canadian Regulations:**

WHMIS Classification : D2A, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**Other Regulations:**

Regulatory VOC (less water and exempt solvent) : 212 g/l

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

**BUTYL BRICK RED - 30 CTG**

Version 3.

Print Date 06/11/2012

REVISION DATE: 12/20/2011

**Legend**

ACGIH - American Conference of Governmental Hygienists

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System