

(11079)

**Material
Safety
Data
Sheet**

MSDS # 414

Latest Revision: September 2012

Page 1 of 5

Selectrode Industries, Inc.




1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME 1140, 2540

1.2 MANUFACTURER

Selectrode Industries, Inc.
230 Broadway
Huntington Station, NY 11746 U.S.A.
Phone: 631-547-5470
Fax: 631-547-5475
E-mail: info@selectrode.com



1.3 EMERGENCY TELEPHONE NUMBER: 631-547-5470

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients:

Important: This section covers the materials of which the products are manufactured. The fumes and gases produced during normal use of this product are covered in Section 3. The term "Hazardous" in "Hazardous Material" should be interpreted as a term required and defined in OSHA Hazard Communication Standard 29CFR 1910-1200 and it does not necessarily imply the existence of hazard. The chemicals or compounds reportable by Section 313 of SARA are marked by the symbol #.

INGREDIENTS	CAS#	% RANGE	OSHA PEL (mg/m ³)	ACGIH-TLV (mg/m ³)	CARCINOGENICITY	R-PHASE
Calcium Carbonate	1317-65-3	1-11	5 (as CaO)	10	NO	
Calcium Fluoride	7789-75-5	1-11	2.5 (as F)	2.5 (as F)	NO	
Iron Oxide	1317-61-9	1-11	15	10	NO	
Graphite	7782-42-5	1-11	15 (total dust)	2	NO	
#Barium Fluoride	7787-32-8	1-11	0.5 (total dust) 2.5 (as F)	0.5 (total dust) 2.5 (as F)	NO	
#Barium Carbonate	513-77-9	5-15	0.5	0.5	NO	
Bentonite	1302-78-9	1-11	NR	NR	NO	
Dolomite	16389-88-1	1-11	15	10	NO	
#Nickel	7440-02-0	63-73	1	1	Yes	R40, R43
Iron	7439-89-6	1-11	10 (as Fe ₂ O ₃)	5 (as Fe ₂ O ₃)	NO	
Sodium Silicate	1344-09-8	1-11	NR	5	NO	

3. HAZARD IDENTIFICATION

Reasonable expected decomposition products from normal use of these products include a complex of the oxides of the materials listed in Section 2, as well as carbon monoxide, carbon dioxide, ozone, and nitrogen oxides (refer to "Characterization of Arc Welding Fume" available from the American Welding Society). THE TLV FOR MANGANESE (0.02 mg/m³) WILL BE REACHED BEFORE THE GENERAL LIMIT FOR WELDING FUMES OF 5 mg/m³ IS REACHED. MONITOR FUMES FOR MANGANESE LEVELS. The only way to determine the true identity of the decomposition products is by sampling and analysis. The composition and quantity of the fumes and gases to which a worker may be overexposed can be determined from a sample obtained from inside the welder's helmet, if worn, or in the worker's breathing zone. See ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes." Available from the American Welding Society.

4. FIRST AID MEASURES Eyes: Flush with water for 15 minutes. Call a physician.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: solid.

Odor: none

pH : non applicable

Melting point: 1560-2000° F, 850-1100° C

Relative density: 6-9 g/cm3

Solubility: insoluble in water

10. STABILITY AND REACTIVITY

STABILITY

Conditions to avoid: not applicable.

Materials to avoid: reacts with acids.

Hazardous decomposition products: unknown.

11. TOXICOLOGICAL INFORMATION

Effects of acute exposure

Toxicity to animals: unknown

Local effects: not applicable.

Inhalation: not applicable for the product. For welding fumes see section 3.

Ingestion: not applicable.

Contact with skin: no adverse effects expected.

CARCINOGENICITY:

Effects of chronic (long-term) overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest X-rays. The severity of the change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on X-rays may be caused by non-work factors such as smoking, etc. Nickel and chromium (in some products) are considered carcinogenic. Long term overexposure to nickel fumes may also cause pulmonary fibrosis and edema. Overexposure to manganese compounds may affect the central nervous

system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait. The effect of manganese on the nervous system is irreversible.

12. ECOLOGICAL INFORMATION

About product: data are unknown
About ingredients: data are unknown.

13. DISPOSAL CONSIDERATIONS

Product: For product elimination, consult recycling companies or appropriate local authority.
Package: May be disposed in approved landfills provided local regulations are observed.

14. TRANSPORT INFORMATION

INTERNATIONAL REGULATIONS:

Land shipment: no hazard
- Rail / route (RID/ADR):

Sea shipment: no hazard

Shipment by air: no hazard

15. REGULATORY INFORMATION

Label CEE: not necessary

Danger symbols and indications:

R-Phrases:


S-Phrases:

16. OTHER INFORMATION

The information in this document is believed to be correct as of the date issued. However, no warranty is expressed to be implied regarding the accuracy or completeness of this information. This information and product are furnished on the condition that the person receiving them shall make his own determinations as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.
This Material Safety Data Sheet complies with the EC directives 91/155/EEC and 93/112/EEC including modifications 2001/58/EC.

**Material
Safety
Data
Sheet**

MSDS # 414
Latest Revision: September 2012
Page 5 of 5
Selectrode Industries, Inc.



Complies with OSHA Communication Standard 29 CFR 1910.1200 and Superfund Amendments and Reauthorization Act (SARA) of 1986 Public Law 99-499

End of the document.