

(11100)



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification


Product ID: AAR0697
Product Name: DURASPAR 430 CNR #12 RED
Product Use: Paint or Coatings Related Product
Effective date: 15/Aug/2011
Revision Date: 15/Aug/2011
UN ID Number (msds): UN1263
WHMIS Classification: D2B Toxic Material D2A Very Toxic Material B2 Flammable Liquids

Company Identification

Valspar, Inc.
1915 Second Street West
Cornwall, Ontario K6H 5T1

Tech Info Phone: 1-613-932-8960

**24-Hour Medical Emergency
Phone:** 1-888-345-5732



2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

- Moderate eye irritation

Skin Contact:

- Causes skin irritation.
- May cause defatting of the skin.
- Dermatitis
- Can be absorbed through skin.
- May cause sensitization by skin contact.

Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause sensitization by inhalation.

Target Organ and Other Health Effects:

- Causes headache, drowsiness or other effects to the central nervous system.
- Liver injury may occur.
- Kidney injury may occur.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.

This product contains ingredients that may contribute to the following potential chronic health effects:

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Possible sensitization.
- Prolonged exposure over TLV may produce pneumoconiosis.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Ingredient Name CAS-No. | Approx. Weight % | Chemical Name | CAS Number |
|--|---------------------|--|------------|
| BARITE 13462-86-7 | 30 - 35 | Barite (Ba(SO ₄)) | 13462-86-7 |
| BUTYL ACETATE 123-86-4 | 5 - 10 | n-Butyl acetate | 123-86-4 |
| DIISOBUTYL KETONE 108-83-8 | 5 - 10 | Diisobutylketone | 108-83-8 |
| ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2 | 1 - 5 | Ethylene glycol, monobutyl ether acetate | 112-07-2 |
| IRON OXIDE 1309-37-1 | 1 - 5 | IRON OXIDE(Fe ₂ O ₃) | 1309-37-1 |
| STODDARD SOLVENT 8052-41-3 | 1 - 5 | Stoddard solvent | 8052-41-3 |
| MINERAL SPIRITS 64742-47-8 | 1 - 5 | Petroleum distillates, hydrotreated light | 64742-47-8 |
| NAPHTHA 64742-89-8 | 1 - 5 | SOLVENT NAPHTHA, PETROLEUM, LIGHT ALIPH | 64742-89-8 |
| NAPHTHA 64742-48-9 | 1 - 5 | Naphtha, petroleum, hydrotreated heavy | 64742-48-9 |
| NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY 64742-82-1 | 1 - 5 | Naphtha, petroleum, hydrodesulfurized heavy | 64742-82-1 |
| 4,6-DIMETHYLHEPTAN-2- ONE 19549-80-5 | 1 - 5 | 2-Heptanone, 4,6- dimethyl- | 19549-80-5 |
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | Titanium dioxide | 13463-67-7 |

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| | | | |
|-----------------------------------|--------|---|-----------|
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | Carbon black | 1333-86-4 |
| COBALT OCTOATE 136-52-7 | .1 - 1 | Hexanoic acid, 2-ethyl-, cobalt(2+) salt | UNKNOWN |

If this section is blank there are no hazardous components per WHMIS guidelines.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|---|
| Flash point (Fahrenheit): | 56 |
| Flash point (Celsius): | 13 |
| Lower explosive limit (%): | 1 |
| Upper explosive limit (%): | 9 |
| Autoignition temperature: | not determined |
| Sensitivity to impact: | no |
| Sensitivity to static discharge: | Subject to static discharge hazards. Please see bonding and grounding information in Section 7. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Chemical goggles, also wear a face shield if splashing hazard exists.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Other Personnel Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|-------------------------------|---------------------|---|-------------------------|-------------------|
| BARITE 13462-86-7 | 30 - 35 | 0.5 mg/m ³ TWA Ba | | |
| BUTYL ACETATE 123-86-4 | 5 - 10 | 150 ppm TWA 710 mg/m ³ TWA | | |
| DIISOBUTYL KETONE 108-83-8 | 5 - 10 | 290 mg/m ³ TWA 50 ppm TWA | | |
| IRON OXIDE 1309-37-1 | 1 - 5 | 10 mg/m ³ TWA fume | | |
| STODDARD SOLVENT 8052-41-3 | 1 - 5 | 2900 mg/m ³ TWA 500 ppm TWA | | |

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|-----------------------------------|---------------------|--|-------------------------|-------------------|
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | 15 mg/m ³ TWA dust total | | |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | 3.5 mg/m ³ TWA | | |

ACGIH Threshold Limit Value (TLV's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|--|---------------------|--|--------------|----------------|----------------------|
| BARITE 13462-86-7 | 30 - 35 | 0.5 mg/m ³ TWA Ba | | | |
| BUTYL ACETATE 123-86-4 | 5 - 10 | 150 ppm TWA | 200 ppm STEL | | |
| DIISOBUTYL KETONE 108-83-8 | 5 - 10 | 25 ppm TWA | | | |
| ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2 | 1 - 5 | 20 ppm TWA | | | |
| IRON OXIDE 1309-37-1 | 1 - 5 | 5 mg/m ³ TWA respirable fraction | | | |
| STODDARD SOLVENT 8052-41-3 | 1 - 5 | 100 ppm TWA | | | |
| NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY 64742-82-1 | 1 - 5 | 100 ppm | | | |
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | 10 mg/m ³ TWA | | | |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | 3.5 mg/m ³ TWA | | | |

9. PHYSICAL PROPERTIES

| | |
|---|-------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | liquid |
| pH: | not determined |
| Vapor pressure: | 103 mmHg @ 100°F (37.78°C) |
| Vapor density (air = 1.0): | 5.5 |
| Boiling point: | not determined |
| Solubility in water: | not determined |
| Coefficient of water/oil distribution: | not determined |
| Density (lbs per US gallon): | 11.3 |
| Specific Gravity: | 1.35 |
| Evaporation rate (butyl acetate = 1.0): | 1.4 |
| Flash point (Fahrenheit): | 56 |
| Flash point (Celsius): | 13 |
| Lower explosive limit (%): | 1 |
| Upper explosive limit (%): | 9 |
| Autoignition temperature: | not determined |

10. STABILITY AND REACTIVITY

10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Conditions to Avoid:

Heat.

Incompatibility:

Strong oxidizing agents

Hazardous Polymerization:

None anticipated.

Hazardous Decomposition Products:

Carbon monoxide and carbon dioxide. Oxides of sulfur.

Sensitivity to static discharge:

Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

| Ingredient Name CAS-No. | Approx. Weight % | NIOSH - Selected LD50s and LC50s |
|--|---------------------|--|
| BARITE 13462-86-7 | 30 - 35 | > 15000 mg/kg Oral LD50 Rat |
| BUTYL ACETATE 123-86-4 | 5 - 10 | = 10768 mg/kg Oral LD50 Rat = 390 ppm Inhalation LC50 Rat 4 h > 17600 mg/kg Dermal LD50 Rabbit |
| DIISOBUTYL KETONE 108-83-8 | 5 - 10 | = 16 g/kg Dermal LD50 Rabbit = 5750 mg/kg Oral LD50 Rat > 2300 ppm Inhalation LC50 Rat 4 h |
| ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2 | 1 - 5 | = 1480 mg/kg Dermal LD50 Rabbit = 1600 mg/kg Oral LD50 Rat |
| IRON OXIDE 1309-37-1 | 1 - 5 | > 10000 mg/kg Oral LD50 Rat |
| MINERAL SPIRITS 64742-47-8 | 1 - 5 | > 2000 mg/kg Dermal LD50 Rabbit > 5.2 mg/L Inhalation LC50 Rat 4 h > 5000 mg/kg Oral LD50 Rat |
| NAPHTHA 64742-89-8 | 1 - 5 | = 3000 mg/kg Dermal LD50 Rabbit = 5000 mg/kg Oral LD50 Mouse |
| NAPHTHA 64742-48-9 | 1 - 5 | > 3160 mg/kg Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat |
| NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY 64742-82-1 | 1 - 5 | > 3160 mg/kg Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat |
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | > 10000 mg/kg Oral LD50 Rat |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | > 15400 mg/kg Oral LD50 Rat > 3 g/kg Dermal LD50 Rabbit |

Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

IARC has classified carbon black as possibly carcinogenic to humans (Group 2B). Contains TiO₂ which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TiO₂ provide an adequate basis to conclude TiO₂ is carcinogenic. TiO₂ is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA. The International Agency For Research On Cancer (IARC) has determined that Cobalt and Cobalt Compounds are substances that are possibly carcinogenic to humans (IARC group 2B).

| Ingredient Name CAS-No. | Approx. Weight % | IARC Group 1 - Human Evidence | IARC Group 2A - Limited Human Data | IARC Group 2B - Sufficient Animal Data |
|-----------------------------------|---------------------|----------------------------------|---------------------------------------|---|
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | | | Monograph 47 [1989] |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | | | Monograph 65 [1996] |
| COBALT OCTOATE 136-52-7 | .1 - 1 | | | Monograph 52 [1991] |

| Ingredient Name CAS-No. | Approx. Weight % | NTP Known Carcinogens | NTP Suspect Carcinogens | NTP Evidence of Carcinogenicity |
|--------------------------------|---------------------|--------------------------|----------------------------|---|
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | | | male rat-negative; female rat-negative; male mice-negative; female mice-negative |

| Ingredient Name CAS-No. | Approx. Weight % | OSHA - Hazard Communication Carcinogens | OSHA - Specifically Regulated Carcinogens | ACGIH Carcinogens |
|---|---------------------|---|--|--|
| ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2 | 1 - 5 | | | A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| TITANIUM DIOXIDE 13463-67-7 | .1 - 1 | Present | | |
| C.I. PIGMENT BLACK 7 1333-86-4 | .1 - 1 | Present | | |
| COBALT OCTOATE 136-52-7 | .1 - 1 | Present | | |

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

Canadian Transport of Dangerous Goods

Proper Shipping Name: PAINT
Hazard Class: 3
UN ID Number (msds): UN1263
Packing Group: II

TDG Clear Language Exceptions:

For Dangerous Goods, the supplier may apply one of the following exceptions (TDG Reference): Limited quantity/Consumer Commodity (1.17), Does not sustain combustion, etc. (2.18), Viscous liquid (2.19), Flammable liquid General Exemption (1.33) or US DOT Reciprocity (9.1,3 & 4). Please consult current TDG regulations before applying any of these exceptions to subsequent shipments.

International Air Transport Association (IATA):

Proper Shipping Name: Paint
Hazard Class: 3

UN ID Number (msds): UN1263
Packing Group: II

International Maritime Organization (IMO):
Proper Shipping Name: PAINT
Hazard Class: 3
IMO UN/ID Number (msds): UN1263
Packing Group: II

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS - Chemical Inventories

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada National Pollutant Release Inventory:

| Ingredient Name CAS-No. | Approx. Weight % | NPRI Status |
|---|---------------------|---------------------------|
| BUTYL ACETATE 123-86-4 | 5 - 10 | Part 5 Substance |
| DIISOBUTYL KETONE 108-83-8 | 5 - 10 | Part 4 Substance |
| ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2 | 1 - 5 | Part 5 Substance |
| IRON OXIDE 1309-37-1 | 1 - 5 | YES |
| STODDARD SOLVENT 8052-41-3 | 1 - 5 | Part 5 Substance |
| MINERAL SPIRITS 64742-47-8 | 1 - 5 | Part 5 Substance |
| NAPHTHA 64742-89-8 | 1 - 5 | Part 5 Substance |
| NAPHTHA 64742-48-9 | 1 - 5 | Part 5 Substance |
| COBALT OCTOATE 136-52-7 | .1 - 1 | Part 1, Group 1 Substance |

16. OTHER INFORMATION

HMIS Codes

Health: 2*
Flammability: 3
Reactivity: 1
PPE: X - See Section 8 for Personal Protective Equipment (PPE).

16. OTHER INFORMATION

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By: Regulatory Affairs Department
Print date: 15/Aug/2011
Revision Date: 15/Aug/2011

Technical Information:

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440
Tech Info Phone: 1-613-932-8960

24-Hour Medical Emergency Phone: 1-888-345-5732