

(11129)

2000.22404 DEVTRAN 224 NEW CLBASE 18.9L

SECTION 1

PRODUCT IDENTIFIER 2000.22404 DEVTRAN 224 NEW CLBASE 18.9L
 NEUTRAL TINT BASE
 DATE OF PREPARATION NOVEMBER 30, 2012
 PRODUCT USE PROTECTIVE COATING
 MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,
 STRONGSVILLE, OHIO 44136, U.S.A
 AKZO NOBEL CANADA INC., 8200 KEELE STREET,
 CONCORD, ONTARIO L4K 2A5, CANADA.
 EMERGENCY AND MSDS TELEPHONE NUMBER:
 1-800-545-2643
 MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT
 AKZO NOBEL PAINTS LLC

APPROVED MATERIAL
 APR 01 2013
 MSDS # 11129
 APPROVED BY *[Signature]*

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	WT. %:
CHEMICAL NAME CASTOR OIL DERIVATIVE COMMON NAME : RHEOLOGICAL ADDITIVE CAS NUMBER: CONFIDENTIAL	1-5
CHEMICAL NAME BENZENE, ETHYL- COMMON NAME : ETHYLBENZENE CAS NUMBER: 100-41-4	.1-1.0
CHEMICAL NAME 2-PENTANONE, 4-METHYL- COMMON NAME : METHYL ISOBUTYL KETONE CAS NUMBER: 108-10-1	5-10
CHEMICAL NAME 1,3,5-TRIMETHYLBENZENE COMMON NAME : 1,3,5-TRIMETHYLBENZENE CAS NUMBER: 108-67-8	1-5
CHEMICAL NAME BENZENE, DIMETHYL- COMMON NAME : XYLENE CAS NUMBER: 1330-20-7	1-5
CHEMICAL NAME CALCIUM METASILICATE COMMON NAME : WOLLASTONITE CAS NUMBER: 13983-17-0	1-5
CHEMICAL NAME TALC COMMON NAME : TALC CAS NUMBER: 14807-96-6	10-20
CHEMICAL NAME QUARTZ COMMON NAME : QUARTZ CAS NUMBER: 14808-60-7	10-20
CHEMICAL NAME OXIRANE, 2,2'-((1-METHYLETHYLIDENE) BIS(4,1-PHENYLENEOXYMETHYLENE)) BIS, HOMOPOLYMER COMMON NAME : EPOXY RESIN CAS NUMBER: 25085-99-8	40-50
CHEMICAL NAME SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC COMMON NAME : LIGHT AROMATIC SOLVENT NAPHTHA CAS NUMBER: 64742-95-6	1-5
CHEMICAL NAME 1-BUTANOL COMMON NAME : N-BUTANOL CAS NUMBER: 71-36-3	1-5
CHEMICAL NAME BENZENE, 1,2,4-TRIMETHYL- COMMON NAME : PSEUDOCUMENE CAS NUMBER: 95-63-6	1-5
CHEMICAL NAME BENZENE, (1-METHYLETHYL)- COMMON NAME : CUMENE CAS NUMBER: 98-82-8	.1-1.0

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.
 EFFECTS OF OVEREXPOSURE
 INHALATION PROLONGED INHALATION MAY LEAD TO MUCOUS MEMBRANE IRRITATION,

FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, ABDOMINAL PAIN, CHEST PAIN, COUGHING, APATHY, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, ALLERGIC RESPONSE, TREMORS, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, DEATH.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, ALLERGIC RESPONSE, SEVERE SKIN IRRITATION. POSSIBLE SENSITIZATION TO SKIN.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION, CORNEAL INJURY.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, MUCOUS MEMBRANE IRRITATION, DROWSINESS, DIZZINESS AND/OR LIGHTEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, VISUAL DISTURBANCES, APATHY, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, BURNS OF THE MOUTH, THROAT, STOMACH, PULMONARY EDEMA, CONVULSIONS, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, DEATH.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
EYE, SKIN, RESPIRATORY DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.
DISPOSE OF CONTAMINATED LEATHER ITEMS, SUCH AS SHOES AND BELTS.
IF IRRITATION OCCURS, CONSULT A PHYSICIAN.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 100 F./ 38 C. LOWER EXPLOSIVE LIMIT 1.1 (%)
UPPER EXPLOSIVE LIMIT 7.0 (%)

FIRE EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, ACRID FUMES, ALDEHYDES, TOXIC GASES, SMOKE AND SOOT. PHENOLICS.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. AVOID CONDITIONS WHICH RESULT IN FORMATION OF INHALABLE PARTICLES SUCH AS SPRAYING OR ABRADING (SANDING) PAINTED SURFACES. IF SUCH CONDITIONS CANNOT BE AVOIDED, USE APPROPRIATE RESPIRATORY PROTECTION AS DIRECTED UNDER EXPOSURE CONTROLS/PERSONAL PROTECTION.

EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

ACGIH (TWA) : 20 PPM OSHA (TWA) : 100 PPM

ACGIH (STEL) : 125 PPM

COMMON NAME : METHYL ISOBUTYL KETONE

CAS NUMBER: 108-10-1

ACGIH (TWA) : 20 PPM OSHA (TWA) : 100 PPM

ACGIH (STEL) : 75 PPM

COMMON NAME : 1,3,5-TRIMETHYLBENZENE

CAS NUMBER: 108-67-8

ACGIH (TWA) : 25 PPM

ACGIH (STEL) : 35 PPM

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

ACGIH (TWA) : 100 PPM OSHA (TWA) : 100 PPM

ACGIH (STEL) : 150 PPM

COMMON NAME : WOLLASTONITE

CAS NUMBER: 13983-17-0

ACGIH (TWA) : 10 MG/M3 OSHA (TWA) : 5 MG/M3

COMMON NAME : TALC

CAS NUMBER: 14807-96-6
 ACGIH(TWA): 2 MG/M3 OSHA(TWA): .1 MG/M3
 COMMON NAME: QUARTZ
 CAS NUMBER: 14808-60-7
 ACGIH(TWA): .025 MG/M3 OSHA(TWA): 0.1 MG/M3
 COMMON NAME: LIGHT AROMATIC SOLVENT NAPHTHA
 CAS NUMBER: 64742-95-6
 OSHA(TWA): 500X PPM
 COMMON NAME: N-BUTANOL
 CAS NUMBER: 71-36-3
 ACGIH(TWA): 20 PPM OSHA(TWA): 100 PPM
 COMMON NAME: CUMENE
 CAS NUMBER: 98-82-8
 ACGIH(TWA): 50 PPM OSHA(TWA): 50 PPM
 OSHA (SKIN) : SKIN CEILING: SUPP REC STD.: NOT AVAILABLE

X AS PETROLEUM DISTILLATES

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

USE EXPLOSION-PROOF EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.

IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, FACE SHIELD, APRON.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.303
BOILING RANGE (F/C):	237-415/114-213	WEIGHT PER GALLON:	10.86/ 13.04IMP
%VOLATILE BY VOLUME:	32.69		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, REDUCING AGENTS, BASES, ALDEHYDES, AMINES, NITRIC ACID, COMBUSTIBLE MATERIALS, MINERAL ACIDS.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, STORAGE NEAR ACIDS, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

MAY POLYMERIZE IN PRESENCE OF ALIPHATIC AMINES.

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : RHEOLOGICAL ADDITIVE

CAS NUMBER: CONFIDENTIAL

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO ACGIH YES A3

LD50: 3500.00 MG/KG ORL RAT

LD50: 15.35 GM/KG SKN RBT

LC50: 17.20 MG/L/4 HR IHL RAT
COMMON NAME : METHYL ISOBUTYL KETONE
CAS NUMBER: 108-10-1
CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO ACGIH YES A3
LD50:> 20.00 GM/KG SKN RBT
LD50: 2080.00 MG/KG ORL RAT
COMMON NAME : 1,3,5-TRIMETHYLBENZENE
CAS NUMBER: 108-67-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LC50: 24.00 GM/M3/4HR IHL RAT
COMMON NAME : XYLENE
CAS NUMBER: 1330-20-7
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50:>1700.00 MG/KG SKN RBT
LD50: 4300.00 MG/KG ORL RAT
LC50: 5000.00 PPM/4HR IHL RAT
COMMON NAME : WOLLASTONITE
CAS NUMBER: 13983-17-0
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
COMMON NAME : TALC
CAS NUMBER: 14807-96-6
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH YES A4
COMMON NAME : QUARTZ
CAS NUMBER: 14808-60-7
CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA NO ACGIH YES A2
COMMON NAME : EPOXY RESIN
CAS NUMBER: 25085-99-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50: 6000.00 MG/KG SKN RBT
LD50:>2400.00 MG/KG ORL RAT
COMMON NAME : LIGHT AROMATIC SOLVENT NAPHTHA
CAS NUMBER: 64742-95-6
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50:> 5.00 GM/KG ORL RAT
LC50:>3670.00 PPM IHL RAT
COMMON NAME : N-BUTANOL
CAS NUMBER: 71-36-3
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50: 790.00 MG/KG ORL RAT
LD50: 2680.00 MG/KG ORL MOU
LD50: 3484.00 MG/KG ORL RBT
LD50: 3400.00 MG/KG SKN RBT
LC50: 8000.00 PPM/4HR IHL RAT
COMMON NAME : PSEUDOCUMENE
CAS NUMBER: 95-63-6
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50: 5.00 GM/KG ORL RAT
COMMON NAME : CUMENE
CAS NUMBER: 98-82-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50: 1400.00 MG/KG ORL RAT
LD50: 12.75 GM/KG ORL MOU

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.
NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN
AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS
MAY BE HARMFUL OR FATAL.
OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER,
KIDNEY, CENTRAL NERVOUS SYSTEM, BLOOD.

CARCINOGENICITY INHALATION OF NON-ASBESTIFORM COSMETIC GRADE TALC FOR

2 YEARS AT 6 AND 18 MG/M3 PRODUCED CLEAR EVIDENCE OF CARCINOGENICITY IN FEMALE RATS (LUNG AND ADRENAL TUMORS) AND SOME EVIDENCE OF CARCINOGENICITY IN MALE RATS (ADRENAL TUMORS). NO EVIDENCE OF CARCINOGENICITY WAS DEMONSTRATED IN MALE AND FEMALE MICE EXPOSED UNDER THE SAME CONDITIONS. MICROSCOPIC EXAMINATION OF THE LUNGS OF RATS AND MICE EXPOSED TO TALC REVEALED ADDITIONAL EXPOSURE RELATED EFFECTS PRIMARILY ASSOCIATED WITH THE INFLAMMATORY RESPONSE. IN LONG TERM (2 YEAR) INHALATION STUDIES, THE NATIONAL TOXICOLOGY PROGRAM (NTP) FOUND CLEAR EVIDENCE OF CARCINOGENIC ACTIVITY IN MICE AND MALE RATS AND SOME EVIDENCE OF CARCINOGENIC ACTIVITY IN FEMALE RATS EXPOSED TO CUMENE.

CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE EVIDENCE FOR CANCER IN EXPOSED HUMANS.

IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED INHALED TALC NOT CONTAINING ASBESTOS OR ASBESTIFORM FIBRES AS NOT CLASSIFIABLE TO ITS CARCINOGENICITY (GROUP 3). PERINEAL USE OF TALC-BASED BODY POWDER IS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B).

REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT UN1263, PAINT, COMBUSTIBLE LIQUID, PGIII
 IMDG UN1263, PAINT, 3, PGIII, LIMITED QUANTITY
 UN1263, PAINT, 3, PGIII
 IATA NOT AVAILABLE
 TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

	SARA	SARA	CERCLA	HAZ AIR	MARINE
	302	313	302.4	POLLUTANT	POLTNT
CAS NUMBER: 100-41-4	NO	YES	YES	YES	NO
COMMON NAME : ETHYLBENZENE					

2000.22404 DEVRAN 224 NEW CLBASE 18.9L

CAS NUMBER:	108-10-1	NO	YES	YES	YES	NO
COMMON NAME :	METHYL ISOBUTYL KETONE					
CAS NUMBER:	1330-20-7	NO	YES	YES	YES	NO
COMMON NAME :	XYLENE					
CAS NUMBER:	71-36-3	NO	YES	YES	NO	NO
COMMON NAME :	N-BUTANOL					
CAS NUMBER:	95-63-6	NO	YES	NO	NO	NO
COMMON NAME :	PSEUDOCUMENE					
CAS NUMBER:	98-82-8	NO	YES	YES	YES	
COMMON NAME :	CUMENE					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.