


# Material Safety Data Sheet




## 1. Product and company identification

**Product name**  Castrol Multi Purpose Chassis Grease  
**MSDS #**  60683  
**Historic MSDS #:**  000002954  
**Code**  60683-CA01 USXX  
**Product use**  Lubricant Grease  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.  
**Manufacturer** BP Lubricants USA, Inc  
1500 Valley Road  
Wayne, NJ USA  
07470  
**Supplier** Wakefield Canada, Limited  
3620 Lakeshore Blvd West  
Toronto, Ontario, Canada  
M8W 1P2  
Phone Number - 416-252-5511  
Fax Number - 416-252-7315  
  
BP Lubricants USA, Inc  
1500 Valley Road  
Wayne, NJ USA  
07470  
Phone Number - 973-633-2296  
Fax Number - 973-633-7475

**EMERGENCY HEALTH INFORMATION:** 1 (800) 447-8735  
Outside the US: +1 703-527-3887 (CHEMTREC)

**EMERGENCY SPILL INFORMATION:** 1 (613) 996-6666 CANUTEC (Canada)

**OTHER PRODUCT INFORMATION** 1 (866) 4 BP - MSDS  
(866-427-6737 Toll Free - North America)  
email: bpcares@bp.com



## 2. Hazards identification

**Physical state**  Grease  
**Color**  Green.  
**Emergency overview**  WARNING !  
 CAUSES EYE AND SKIN IRRITATION.  
MAY CAUSE RESPIRATORY TRACT IRRITATION.  
 Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

**Routes of entry**  Dermal contact. Eye contact. Inhalation.

**Potential health effects**

**Eyes**  Causes eye irritation.

**Skin**  Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

**Inhalation**  May cause respiratory tract irritation.

See toxicological information (Section 11)

### 3. Composition/information on ingredients

Ingredient name	CAS #	%
Base oil - highly refined	Varies	85 - 90
Zinc alkyl dithiophosphate	68649-42-3	1 - 5

### 4. First aid measures

Eye contact	<input checked="" type="checkbox"/> In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin contact	<input checked="" type="checkbox"/> Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Inhalation	<input checked="" type="checkbox"/> Inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	<input checked="" type="checkbox"/> Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.
Notes to physician	<input checked="" type="checkbox"/> Treatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

### 5. Fire-fighting measures

Flash point	<input checked="" type="checkbox"/> Open cup: 246°C (474.8°F) [Cleveland.]
Fire/explosion hazards	<input checked="" type="checkbox"/> In a fire or if heated, a pressure increase will occur and the container may burst.
<u>Extinguishing media</u>	
Suitable	<input checked="" type="checkbox"/> Use an extinguishing agent suitable for the surrounding fire.
Not suitable	<input checked="" type="checkbox"/> Do not use water jet.
Fire-fighting procedures	<input checked="" type="checkbox"/> Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous combustion products	<input checked="" type="checkbox"/> Combustion products may include the following: phosphorus oxides metal oxide/oxides carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) sulfur oxides (SO, SO <sub>2</sub> etc.)
Protective clothing (fire)	<input checked="" type="checkbox"/> Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions	<input checked="" type="checkbox"/> No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	<input checked="" type="checkbox"/> Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
<u>Methods for cleaning up</u>	

<b>Large spill</b>	<p>Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.</p>
<b>Small spill</b>	<p>Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p>

## 7. Handling and storage

<b>Handling</b>	<p>Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.</p>
<b>Storage</b>	<p>Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.</p>
<b>Other information</b>	<p>Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on the sense of smell to detect hydrogen sulfide.</p>

## 8. Exposure controls/personal protection

### Occupational exposure limits

Ingredient name	Occupational exposure limits
Base oil - highly refined	<p><b>CA Alberta Provincial (Canada).</b>            15 min OEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 7/2009 Form: Mist            8 hrs OEL: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 4/2004 Form: Mist  <b>CA Quebec Provincial (Canada).</b>            STEV: 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/2000 Form: mist            TWAEV: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/2000 Form: mist  <b>CA Ontario Provincial (Canada).</b>            TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1992 Form: mist            STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/1992 Form: mist</p>

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

<b>Control Measures</b>	<p>Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.</p>
<b>Hygiene measures</b>	<p>Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.</p>
<b>Personal protection</b>	
<b>Eyes</b>	<p>Avoid contact with eyes. Safety glasses with side shields or chemical goggles.</p>
<b>Skin and body</b>	<p>Do not get on skin or clothing. Wear suitable protective clothing.</p>
<b>Respiratory</b>	<p>Use adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.</p>

manus

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

## 9. Physical and chemical properties

Physical state	Grease
Color	Green.
Odor	Mild. Petroleum
Odor threshold	Not available.
Flash point	Open cup: 246°C (474.8°F) [Cleveland.]
Specific gravity	0.9
pH	Not available.
Boiling point / Range	Not available.
Melting point / Range	Not available.
Vapor pressure	0.013 kPa (<0.1 mm Hg) at 20°C
Vapor density	Not available.
Evaporation rate	0.01 (butyl acetate = 1)
Solubility	Insoluble in water.
LogK <sub>ow</sub>	Not available.

## 10. Stability and reactivity

Stability and reactivity	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	This product may release hydrogen sulfide (H <sub>2</sub> S) if it is heated to high temperatures.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11. Toxicological information

### Potential chronic health effects

Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Reproductive effects	No known significant effects or critical hazards.
Medical conditions aggravated by over-exposure	None known.

## 12. Ecological information

### Ecotoxicity

No testing has been performed by the manufacturer.

## 13. Disposal considerations

### Waste information

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

## 15. Regulatory information

### WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Other regulations

#### Canada inventory

All components are listed or exempted.

#### United States inventory (TSCA 8b)

All components are listed or exempted.

#### REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

#### Australia inventory (AICS)

All components are listed or exempted.

#### China inventory (IECSC)

All components are listed or exempted.

#### Japan inventory (ENCS)

At least one component is not listed.

#### Korea inventory (KECI)

All components are listed or exempted.

#### Philippines inventory (PICCS)

All components are listed or exempted.

## 16. Other information

### Label requirements

WARNING !

CAUSES EYE AND SKIN IRRITATION.  
 MAY CAUSE RESPIRATORY TRACT IRRITATION.

### History

#### Date of issue

02/11/2013.

#### Date of previous issue

02/09/2013.

#### Prepared by

Product Stewardship

Indicates information that has changed from previously issued version.

Product name  Castrol Multi Purpose Chassis Grease

Product code  60683-CA01 USXX Page: 5/6

Version 2 Date of issue 02/11/2013.

Format Canada

Language ENGLISH

(Canada)

(ENGLISH)

**Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name **Castrol Multi Purpose Chassis Grease**

Product code **460683-CA01 USXX** Page: 6/6

Version 2 Date of issue 02/11/2013.

Format **Canada**

Language **ENGLISH**

(Canada)

(ENGLISH)