

HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract. Prolonged inhalation may lead to loss of appetite, mucous membrane irritation, fatigue, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, blurred vision, coughing, difficulty with speech, central nervous system depression, intoxication, anesthetic effect or narcosis, difficulty of breathing, allergic response, asthmatic reaction, tremors, severe lung irritation or damage, liver damage, kidney damage, convulsions, pneumoconiosis, loss of consciousness, respiratory failure, asphyxiation, death. Possible sensitization to respiratory tract.

Skin contact : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering, allergic response. Skin contact may result in dermal absorption of component(s) of this product which may cause central nervous system depression.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, redness of eyes, severe eye irritation.

Ingestion : Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mouth and throat irritation, mucous membrane irritation, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, central nervous system depression, intoxication, difficulty of breathing, abnormal blood pressure, liver damage, kidney damage, pulmonary edema, convulsions, loss of consciousness.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders, lung disorders, asthma-like conditions, kidney disorders, liver disorders.

FIRST-AID MEASURES (ANSI Section 4)

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort. Get medical attention if discomfort or irritation persists.

Skin contact : Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs, consult a physician.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES (ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may explode when exposed to extreme heat or fire. Vapors may ignite explosively at ambient temperatures. Vapors are heavier than air and may travel long distances to a source of ignition and flash back. Vapors can form explosive mixtures in air at elevated temperatures. Closed containers may burst if exposed to extreme heat or fire. Dust explosion hazard. Solvent must not be allowed to evaporate because contact of water with aluminum dust generates hydrogen, which is a flammable gas. May decompose under fire conditions emitting irritant and/or toxic gases. Rags, steel wool or waste soaked with this material may spontaneously catch fire if improperly discarded. Immediately after use, place soaked rags, steel wool or waste in a sealed water-filled metal container.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide, oxides of nitrogen, acrolein, oxides of sulfur, ammonia, aldehydes, aluminum oxide, toxic gases, nitrogen, monoazo compounds, aromatic amines, 3,3' dichlorobenzidine. Oxides of calcium, acid halides, smoke.

ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Ventilate area with explosion-proof equipment. Spills may be collected with absorbent materials. Use non-sparking tools. Evacuate all unnecessary personnel. Place collected material in proper container. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE (ANSI Section 7)

Handling and storage : Store below 80f. Store below 100f (38c). Keep away from heat, sparks and open flame. Keep from freezing.

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumulations.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection : Where respiratory protection is required, use only NIOSH/MSHA approved respirators in accordance with OSHA standard 29 CFR 1910.134.

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors. Use explosion-proof equipment. Use non-sparking equipment.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing, apron.

STABILITY AND REACTIVITY (ANSI Section 10)

Under normal conditions : Stable stable below 212 f (100 c). See section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, reducing agents, bases, halogens, amines, ammonium salts, peroxides, nitric acid, organic materials, halogenated compounds, combustible materials. Nitrates. Acetaldehyde styrene monomer.

Conditions to avoid : Elevated temperatures, driers, contact with oxidizing agent, sparks, open flame, ignition sources.

Hazardous polymerization : Will not occur

The information contained herein is based on data available at the time of preparation of this data sheet which Akzo Nobel Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Akzo Nobel Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR1910.1200.

TOXICOLOGICAL INFORMATION

(ANSI Section 11)

Supplemental health information : Contains a chemical that may be absorbed through skin. Notice - reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains iron oxide, repeated or prolonged exposure to iron oxide dust may cause siderosis, a benign pneumoconiosis. Other effects of overexposure may include toxicity to liver, kidney, lungs, central nervous system.

Carcinogenicity : Stoddard solvent ic has been shown to cause kidney tumors in male rats in a national toxicology program (NTP) study. These tumors were associated with a specific protein, alpha-2-microglobulin. Because humans do not produce this protein stoddard solvent ic has not been classified as a human carcinogen. Decomposition of diarylide pigments at temperatures above 392f (200c) can produce trace amounts of monoazo dyes, which can then decompose to produce aromatic amines. As the temperature increases into the 464-572f (240-300c), trace quantities of 3,3'-dichlorobenzidine (3,3'-dcb) can be detected. The national toxicology program (NTP) has classified 3,3'-dcb as a known human carcinogen. The international agency for research on cancer (IARC) has classified 3,3'-dcb as a possible human carcinogen (group 2b: sufficient animal data, inadequate human data). In 2-year feed studies of c.I. Pigment red 3, there was some evidence of carcinogenic activity in male rats (adrenal gland - benign pheochromocytomas) and female rats (hepatocellular adenomas). There was also some evidence of carcinogenic activity in male mice (adenomas of renal cortex and thyroid gland), but no evidence in female mice. The international agency for research on cancer (IARC) has classified carbon black as possibly carcinogenic to humans (group 2b) based on sufficient evidence in animals and inadequate evidence in humans. The international agency for research on cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (group 2b) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. In a 2 year inhalation study conducted by the national toxicology program (NTP), ethylbenzene vapor at 750 ppm produced kidney and testicular tumors in rats and lung and liver tumors in mice. Genetic toxicity studies showed no genotoxic effects. The relevance of these results to humans is not known. The international agency for research on cancer (IARC) has classified cobalt and certain cobalt compounds as possibly carcinogenic to humans (group 2b). Injection of metallic cobalt, cobalt alloys, and certain cobalt compounds has resulted in the development of localized tumors in laboratory animals. In a 2-year inhalation bioassay conducted by the national toxicology program (NTP), ethylene glycol butyl ether

(egbe) caused an increased incidence of liver tumors in male mice and forestomach tumors in female mice exposed to 250 ppm, the highest concentration tested with mice. In rats, an increased incidence of tumors affecting the adrenal gland was seen in females exposed at 125 ppm only. This finding was not statistically significant. No increased incidence of any tumor type was seen in male rats exposed to the highest test concentration of 125ppm. The relevance of these findings to humans is unclear. In a lifetime inhalation study, exposure to 250 mg/m3 titanium dioxide resulted in the development of lung tumors in rats. These tumors occurred only at dust levels that overwhelmed the animals' lung clearance mechanisms and were different from common human lung tumors in both type and location. The relevance of these findings to humans is unknown but questionable. The international agency for research on cancer (IARC) has classified titanium dioxide as possibly carcinogenic to humans (group 2b) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. C.I. Pigment 5 showed weak hepatocarcinogenic potential in female rats and in male mice. In the female rats, the liver carcinogenicity was accompanied by hepatotoxicity. Contains methyl ethyl ketoxime (meko). In a lifetime, inhalation study, liver carcinomas were observed in rodents exposed to meko. The relevance to humans is unknown.

Reproductive effects : High exposures to xylene in some animal studies, often at maternally toxic levels, have affected embryo/fetal development. The significance of this finding to humans is not known.

Mutagenicity : C.I. Pigment red was found to be mutagenic with and without metabolic activation in salmonella/microsome studies. In vivo tests and in vitro tests on mammalian cells were negative for mutagenicity.

Teratogenicity : No teratogenic effects are anticipated

ECOLOGICAL INFORMATION

(ANSI Section 12)

No ecological testing has been done by akzo nobel paints llc on this product as a whole.

DISPOSAL CONSIDERATIONS

(ANSI Section 13)

Waste disposal : Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

REGULATORY INFORMATION

(ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data

(ANSI Sections 1, 9, and 14)

| Product Code | Description | Wt. / Gal. | VOC gr. / ltr. | % Volatile by Volume | Flash Point | Boiling Range | HMIS | DOT, proper shipping name |
|--------------|---|------------|----------------|----------------------|-------------|---------------|------|---------------------------------------|
| 4308-6110 | devguard 4308 alkyd industrial gloss enamel - machine gray | 8.16 | 446.89 | 56.69 | 106 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-6650 | devguard 4308 alkyd industrial gloss enamel - medium green | 7.84 | 443.60 | 56.39 | 109 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-7370 | devguard 4308 alkyd industrial gloss enamel - warm brown | 8.25 | 448.50 | 57.01 | 100 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-7460 | devguard 4308 alkyd industrial gloss enamel - architectural brown | 8.33 | 447.55 | 56.92 | 105 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| *4308-7850 | devguard 4308 alkyd industrial gloss enamel - imperial blue | 7.81 | 420.83 | 53.59 | 104 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-8600 | devguard 4308 alkyd industrial gloss enamel - medium yellow | 8.28 | 438.73 | 55.87 | 106 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-9000 | devguard 4308 alkyd industrial gloss enamel - safety red | 7.82 | 437.95 | 55.79 | 105 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-9020 | devguard 4308 alkyd industrial gloss enamel - aluminum | 7.46 | 492.11 | 65.20 | 70 f | 240-365 | *340 | UN1263,paint,3,PGII |
| 4308-9200 | devguard 4308 alkyd industrial gloss enamel - safety orange | 8.04 | 448.00 | 56.92 | 102 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-9400 | devguard 4308 alkyd industrial gloss enamel - safety yellow | 8.33 | 433.84 | 55.33 | 106 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-9700 | devguard 4308 alkyd industrial gloss enamel - safety green | 7.89 | 442.44 | 55.87 | 106 f | 104-415 | *320 | UN1263,paint,combustible liquid,PGIII |
| 4308-9990 | devguard 4308 alkyd industrial gloss enamel - black | 7.75 | 422.82 | 53.94 | 102 f | 277-415 | *320 | UN1263,paint,combustible liquid,PGIII |

Ingredients

Product Codes with % by Weight (ANSI Section 2)



| Chemical Name | Common Name | CAS. No. | 4308-6110 | 4308-6650 | 4308-7370 | 4308-7460 | 4308-7850 | 4308-8600 | 4308-9000 | 4308-9020 | 4308-9200 | 4308-9400 | 4308-9700 | 4308-9990 |
|--|---|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| benzene, ethyl- | ethylbenzene | 100-41-4 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 |
| benzene, 1,4-dimethyl- | para-xylene | 106-42-3 | | .1-1.0 | | | .1-1.0 | .1-1.0 | .1-1.0 | | | .1-1.0 | .1-1.0 | .1-1.0 |
| benzene, 1,3-dimethyl- | 1,3-dimethylbenzene | 108-38-3 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 |
| ethanol, 2-butoxy- | 2-butoxyethanol | 111-76-2 | | | | | | | | | | | | .1-1.0 |
| 1,2-benzenedicarboxylic acid, bis (2-ethylhexyl) ester | di (2-ethylhexyl) phthalate | 117-81-7 | | | | | | .01-1 | | | | | | |
| limestone | limestone | 1317-65-3 | | | | 5-10 | | | | | | | | |
| benzene, dimethyl- | xylene | 1330-20-7 | 1-5 | 1-5 | 1-5 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | 1-5 | .1-1.0 | .1-1.0 | 1-5 | .1-1.0 |
| iron oxide | iron oxide | 1332-37-2 | | | 1-5 | 1-5 | | | | | | | | |
| kaolin | clay | 1332-58-7 | | | | | | 1-5 | | | | 1-5 | | |
| carbon black | carbon black | 1333-86-4 | .1-1.0 | | .1-1.0 | 1-5 | .1-1.0 | | | | | | | 1-5 |
| titanium oxide | titanium dioxide | 13463-67-7 | 5-10 | 1-5 | .1-1.0 | 1-5 | 1-5 | 5-10 | | | 1-5 | 5-10 | 1-5 | |
| butanamide, 2-((4-chloro-2-nitrophenyl)azo)- n-(2-methoxyphenyl)-3-oxo- | c.i. pigment yellow 73 | 13515-40-7 | | 1-5 | | | | 1-5 | | | 1-5 | 5-10 | | |
| hexanoic acid, 2-ethyl-, cobalt(2+) salt | cobalt alkanoate | 136-52-7 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | .1-1.0 | |
| copper, {29h, 31h-phthalocyaninato(2-)}n29,n30,n31, n32)-(sp-4-1)- | phthalocyanine blue pigment | 147-14-8 | | | | | 1-5 | | | | | | | |
| 2-naphthalenol, 1-((4-methyl-2-nitrophenyl)azo)- | pigment red 3 | 2425-85-6 | | | | | | | 5-10 | | | | | |
| neodecanoic acid, cobalt salt | cobalt neodecanoate | 27253-31-2 | | | | | | | | | | | .1-1.0 | .1-1.0 |
| 2-naphthalenol, 1-((2,4-dinitrophenyl)azo)- | dinitroaniline orange | 3468-63-1 | | | | | | | | | 1-5 | | | |
| c.i. pigment yellow 42 | yellow iron oxide | 51274-00-1 | | | 5-10 | 1-5 | | | | | | | | |
| butanamide, 2,2'-((3,3'-dichloro(1,1'-biphenyl)- 4,4'-diyl)bis(azo))bis(n-(4-chloro-2,5- dimethoxyphenyl)-3-oxo- | diazo yellow | 5567-15-7 | | | | | | 1-5 | | | | | | |
| butanamide, 2-((2-methoxy-4-nitrophenyl)azo)-n-(2-methoxyphenyl)-3-oxo- | pigment yellow 74 | 6358-31-2 | | | | | | | | | | | 1-5 | |
| solvent naphtha (petroleum), medium aliphatic | medium aliphatic solvent naphtha | 64742-88-7 | 5-10 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 5-10 | 10-20 | 10-20 | 5-10 | 10-20 |
| solvent naphtha (petroleum), light aliphatic | light aliphatic solvent naphtha (petroleum) | 64742-89-8 | | | | | | | | 40-50 | | | | |
| linseed oil, polymerized | linseed oil | 67746-08-1 | | | | | | | | 10-20 | | | | |
| quaternary ammonium compounds, bis(hydrogenated tallow alkyl)di=methyl, salts with bentonite | dispersant, organoclay | 68953-58-2 | | 1-5 | 1-5 | 1-5 | | 1-5 | 1-5 | | | 1-5 | | |
| fatty acids, c9-c13-neo-, cobalt salts | fatty acids, c9-c13-neo-, cobalt salts | 68955-83-9 | | | | | | | | | | | .1-1.0 | |
| benzene | benzene | 71-43-2 | | | | | | | | LT .01 | | | | |
| aluminum | aluminum | 7429-90-5 | | | | | | | | 5-10 | | | | |
| stoddard solvent | mineral spirits | 8052-41-3 | 30-40 | 30-40 | 30-40 | 20-30 | 20-30 | 20-30 | 20-30 | 1-5 | 30-40 | 20-30 | 30-40 | 20-30 |
| benzene, 1,2-dimethyl- | ortho-xylene | 95-47-6 | | .1-1.0 | | | .1-1.0 | .1-1.0 | .1-1.0 | | | .1-1.0 | | .1-1.0 |
| alkyd resin | alkyd resin | Sup. Conf. | 30-40 | 20-30 | 20-30 | 20-30 | 10-20 | 10-20 | 20-30 | | 20-30 | 10-20 | 30-40 | 10-20 |
| rheological additive | rheological additive | Sup. Conf. | | | | | | | | | | | | 1-5 |
| petroleum hydrocarbon resin | petroleum hydrocarbon resin | Sup. Conf. | | | | | | | | 10-20 | | | | |
| long oil alkyd resin | long oil alkyd resin | Sup. Conf. | 5-10 | 10-20 | 10-20 | 10-20 | 30-40 | 20-30 | 20-30 | | 10-20 | 20-30 | 10-20 | 30-40 |

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

| Common Name | CAS. No. | ACGIH-TLV | | | | OSHA-PEL | | | | S.R. Std. | S2 | S3 | CC | H | M | N | I | O |
|---|------------|------------|----------|----------|----------|------------|----------|----------|----------|-----------|----|----|----|---|---|---|---|---|
| | | 8-Hour TWA | STEL | C | S | 8-Hour TWA | STEL | C | S | | | | | | | | | |
| ethylbenzene | 100-41-4 | 100 ppm | 125 ppm | not est. | not est. | 100 ppm | not est. | not est. | not est. | not est. | n | y | y | y | n | n | y | n |
| para-xylene | 106-42-3 | 100 ppm | 150 ppm | not est. | not est. | 100 ppm | not est. | not est. | not est. | not est. | n | y | y | y | n | n | n | n |
| 1,3-dimethylbenzene | 108-38-3 | 100 ppm | 150 ppm | not est. | not est. | 100 ppm | not est. | not est. | not est. | not est. | n | y | y | y | n | n | n | n |
| 2-butoxyethanol | 111-76-2 | 20 ppm | not est. | not est. | not est. | 50 ppm | not est. | not est. | y | not est. | n | y | n | n | n | n | n | n |
| di (2-ethylhexyl) phthalate | 117-81-7 | 5 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | y | y | y | n | y | y | n |
| limestone | 1317-65-3 | 10 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| xylene | 1330-20-7 | 100 ppm | 150 ppm | not est. | not est. | 100 ppm | not est. | not est. | not est. | not est. | n | y | y | y | n | n | n | n |
| iron oxide | 1332-37-2 | 5 mg/m3 | not est. | not est. | not est. | 10 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| clay | 1332-58-7 | 2 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| carbon black | 1333-86-4 | 3.5 mg/m3 | not est. | not est. | not est. | 3.5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| titanium dioxide | 13463-67-7 | 10 mg/m3 | not est. | not est. | not est. | 10 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | y | n |
| c.i. pigment yellow 73 | 13515-40-7 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| cobalt alkanoate | 136-52-7 | .02 mg/m3 | not est. | not est. | not est. | .05 mg/m3 | not est. | not est. | not est. | not est. | n | y | n | y | n | n | n | n |
| phthalocyanine blue pigment | 147-14-8 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| pigment red 3 | 2425-85-6 | 10 mg/m3 | not est. | not est. | not est. | 15 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| cobalt neodecanoate | 27253-31-2 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | y | n | y | n | n | y | n |
| dinitroaniline orange | 3468-63-1 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| yellow iron oxide | 51274-00-1 | 5 mg/m3 | not est. | not est. | not est. | 10 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| diazo yellow | 5567-15-7 | 10 mg/m3 | not est. | not est. | not est. | 15 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| pigment yellow 74 | 6358-31-2 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| medium aliphatic solvent naphtha | 64742-88-7 | 100 ppm | not est. | not est. | not est. | 500 x ppm | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| light aliphatic solvent naphtha (petroleum) | 64742-89-8 | not est. | not est. | not est. | not est. | 300 ppm | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| linseed oil | 67746-08-1 | not est. | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| dispersant, organoclay | 68953-58-2 | 10 mg/m3 | not est. | not est. | not est. | 15 mg/m3 | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| fatty acids, c9-c13-neo-, cobalt salts | 68955-83-9 | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | y | n | y | n | n | n | n |
| benzene | 71-43-2 | .5 ppm | 2.5 ppm | not est. | y | 1 ppm | 5 ppm | not est. | not est. | not est. | n | y | y | y | n | y | y | y |
| aluminum | 7429-90-5 | 1 mg/m3 | not est. | not est. | not est. | 5 mg/m3 | not est. | not est. | not est. | not est. | n | y | n | n | n | n | n | n |
| mineral spirits | 8052-41-3 | 100 ppm | not est. | not est. | not est. | 500 ppm | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| ortho-xylene | 95-47-6 | 100 ppm | 150 ppm | not est. | not est. | 100 ppm | not est. | not est. | not est. | not est. | n | y | y | y | n | n | n | n |
| rheological additive | Sup. Conf. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |
| petroleum hydrocarbon resin | Sup. Conf. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | not est. | n | n | n | n | n | n | n | n |

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable
not est=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=IARC, O=OSHA, y=yes, n=no

APPROVED MATERIAL

OCT 31 2011

MSDS # 11142

APPROVED BY [Signature]

