

10/25/11

MATERIAL SAFETY DATA SHEET

Page 1 of 4

(11143)

MANUFACTURER'S NAME:
Williams-Hayward Protective Coatings, Inc
7425 West 59th Street
Summit, IL 60501

EMERGENCY TELEPHONE:
800-424-9300

INFORMATION TELEPHONE:
708-458-0015

EFFECTIVE DATE: 04/23/03

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER : 22-13089CN
PRODUCT NAME : CN#12 RED/BROWN
CHEMICAL NAME : ORGANIC COATING
CHEMICAL FAMILY: WATER EMULSION AIR DRY COATING

HMIS RATING: H F R PP
2 0 0 J

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT DESCRIPTION	CAS NUMBER	PERCENT BY WGT	ACGIH TLV	OSHA PEL AND OTHER EXPOSURE LIMITS
WATER (NON-HAZARDOUS)	7732-18-5	53.0	NR	NR
ESTER-ALCOHOL	25265-77-4	5.8	835.00 UG/M3	NR

RCRA TRACE ELEMENTS

SECTION III - PHYSICAL DATA

BOILING RANGE: 167 TO 900 (deg F) % VOLATILE (VOLUME): 64.76
75 TO 482 (deg C) % NVM (WEIGHT): 39.07
VAPOR DENSITY: HEAVIER THAN AIR % NVM (VOLUME): 35.23
EVAP RATE: SLOWER THAN BUTYL ACETATE
DENSITY: 8.77 (lb/gl) VOC (less water): 1.60 (lb/gl)
1.05 (kg/l) 192.63 (gr/l)
SOLVENTS: 8.285 (lb/gl) VOC (as shipped): .70 (lb/gl)
.99 (kg/l) 84.93 (gr/l)

APPEARANCE: RED IN COLOR
ODOR: SLIGHT AMINE ODOR
WATER SOLUBLE: YES

APPROVED MATERIAL

OCT 31 2011

MSDS # 11143

APPROVED BY *[Signature]*

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: PAINT, NON FLAMMABLE LIQUID

FLASH POINT: NOT APPLICABLE LEL: N/A UEL: N/A

EXTINGUISHING MEDIA:

For dried film: Carbon Dioxide, dry chemical and water fog.

UNUSUAL FIRE AND EXPLOSION DATA:

Acrylic emulsions will not burn. They may splatter if temperature exceeds boiling point (212 degrees F, 100 degrees C). Dried polymer films are capable of burning.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

INHALATION: Vapor or mist can cause headache, nausea, and irritation of the nose, throat, and lungs. Overexposure can have narcotic effect

EYE CONTACT: Slightly irritating to eyes.

SKIN CONTACT: Irritating to skin upon repeated or prolonged contact.

PRIMARY ROUTES OF ENTRY: Dermal, Inhalation, Ingestion.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Allergy, Asthma, Bronchitis, Emphysema.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION Remove to fresh air. If not breathing, give artificial respiration. Have a trained person administer oxygen.
CALL A PHYSICIAN.

EYE CONTACT Wash with plenty of water for 5 minutes.

SKIN CONTACT Wash with soap and water. An emollient cream or lotion is beneficial.

INGESTION DO NOT SWALLOW. If swallowed, do not induce vomiting.
CALL A PHYSICIAN.

SECTION VI - REACTIVITY DATA

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition may yield oxides of carbon, oxides of nitrogen and low molecular weight hydrocarbons. In baking systems, formaldehyde and ammonia may be present.

CONDITIONS TO AVOID: Non Applicable.

INCOMPATIBILITY (MATERIALS TO AVOID):

Avoid contact with strong oxidizing agents.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep unnecessary people away. Dike and contain spill with inert material (dry sand, fuller's earth, etc) and transfer the liquid to containers for recovery or proper disposal. Floor may be slippery. Care should be exercised to avoid falls.

NOTE: Emulsions can be coagulated by stepwise addition of lime and ferric sulfate to clear water end point.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state, and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Follow OSHA Regulation 29CFR 1910.134 for Respiratory use. Use air-purifying respirator that respirator supplier has demonstrated to be effective for solvent vapors, when concentrations exceed the TLV up to the maximum level at which the respirator is effective. If the concentration of solvents is not known or exceeds the level at which the air-purifying respirator is effective, a positive pressure air supplied respirator (TC19C NIOSH/MSHA) is recommended.

VENTILATION:

Mechanical Local exhaust at point of contaminant (vapor, mist, or dust) release.

PROTECTIVE GLOVES:

Usual hand protection for paint application

EYE PROTECTION:

Splash-proof safety goggles (ANSI Z87.1, 1968).

OTHER PROTECTIVE EQUIPMENT:

Eyewash station, emergency shower.

 SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Indoor:	YES	Refrigerated:	NO
Heated:	YES	Outdoor:	NO

Storage Temperature:	Max. 100 F	Min. 40 F
	Max. 37 C	Min. 4 C

OTHER PRECAUTIONS:

Spray from emulsions must not be inhaled. Respirators should be provided if engineering controls are not adequate. Inhalation exposures to mists or dusts of acrylic polymer should be maintained at (LESS THAN) 10 mg/m³ 8-hour TWA limit established for nuisance dusts.

Residual monomer content under conditions to normal handling present no problems. However, high levels of monomer vapors can be released into workroom atmosphere when emulsions are heat cured or dried (rollers, ovens, infrared lamp, etc) if proper ventilation is not used.

MISCELLANEOUS:

Precautionary Labeling: KEEP FROM FREEZING
 PRODUCT STABILITY MAY BE AFFECTED

 SECTION X - OTHER INFORMATION

SECTION 313 SUPPLIER NOTIFICATION:


This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

Chemical Name	CAS Number	Percent by weight
---------------	------------	-------------------

EUROPEAN INVENTORY STATUS (EINECS):

All components are either listed or are exempt from being listed on the EINECS chemical inventory

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF WILLIAMS-HAYWARD PROTECTIVE COATINGS, INC.'s (WHPC) KNOWLEDGE. The methods or conditions of handling, storage, use, and disposal of this product are beyond our control. WE THEREFORE ASSUME NO RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE, OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE, OR DISPOSAL OF THE PRODUCT!



Williams-Hayward International Coatings, Inc

7425 West 59th Street • Summit, Illinois 60501

US: Mobil 001(708) 267-9821 • Poland: Tel 00(48) 505-141-723
Mexico: Tel 001(708) 267-7671 • Canada: Tel 001(905) 330-3716

Tel 001(708) 458-0014 • Fax 001(708) 461-6266
www.williams-hayward.com

10/25/11

TECHNICAL BULLETIN

PRODUCT DESCRIPTION

Product Type : Non-Flammable Water Emulsion Coatings
Product Name: 22-13089CN CN#12 RED/BROWN

TECHNICAL DATA

60 deg Gardner Gloss:	80	% Solids (weight):	39.071 (+/- 2%)
Viscosity:	6200CPS (+/- 10%)	% Solids (volume):	35.231 (+/- 2%)
pH:	9.0 (+/- 0.8)	Density:	8.776 (lb/gl), 1.05 (gr/ml)
Flash Point:	N/A	VOC (as used):	709 (lb/gl), 84.93 (gr/l)
DOT-HM 102 10:	NONFLAMMABLE	L, a, b :	20.56, 18.00, 10.10
Freeze Thaw Stability:	NONE		

APPLICATION DATA

Bake Temperature:	110-120 F, 43-48 C
Bake Time:	60-120 MINS.
Reduction:	NA
Reducer:	WATER
Tack Free:	60 MINS TO TOUCH (74 deg F, 23 deg C)
Pot Life:	NA
Tip Size:	For airless spray, use 6/17-6/19 tips @ 1500-1800 psi, 103-124 bar
Theoretical Coverage:	565 (sq ft/gal/1 dry mil), 14 (sq m/liter/25 microns)
Application Method:	AIRLESS
Substrate:	COLD & HOT ROLLED STEEL
Surface Preparation:	SSPC-SP-6, SA 2.0
Storage Temperature:	40-90 F, 4-32 C

SPECIAL INSTRUCTIONS

DO NOT FREEZE. STORE AT TEMPS. > 40 degs. F < 100 degs F. FOR OPTIMUM FLOW AND LEVELING USE 6/17-6/19 TIPS @ 1500-1800 PSI. APPLY THE COATING IN TANDUM USING A CROSSCOAT PATTERN. ALLOW A MINIMUM OF 6-8 HOURS DRY TIME PRIOR TO EXPOSING TO RAIN OR FREEZING TEMPERATURES.

The information presented here is based on carefully conducted laboratory tests and is believed to be accurate. However, results can not be guaranteed and it is suggested that customers confirm results in their own laboratory before plant tests are made. Nothing contained in this bulletin shall be construed as a recommendation to use any product or process in violation of the claims of any patent now in effect.

WHPC is an ISO 9001 and AAPM-1003 certified company
with ANSI-RAB, UKAS and RVA accreditation held through ISO 9001 certification by NQA USA Inc.
* WHPC Canada, Mexico, Poland