

(11149)

Material Safety Data Sheet



Revision Number: 002.2

Issue date: 02/28/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Fixmaster Fast Set Steel Putty
Product use: Epoxy Hardener

IDH number: 702088
Item number: 39917_220000
Region: Canada

Company address:
Henkel Corporation
2225 Meadowpine Boulevard
Mississauga, Ontario L5N 7P2

Contact information:
Telephone: 905.814.6511
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste
Color: White
Odor: Pungent
WHMIS hazard class: D.2.A, D.2.B

WARNING: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. Vomiting.
Skin contact: Mild skin irritation. Redness. May be harmful if absorbed through skin.
Eye contact: Mild eye irritation. Redness. May injure eye tissue if not removed promptly.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: Skin disorders. Eye disorders.


See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polymercaptan hardener	Proprietary	30 - 60
Quartz (SiO2)	14808-60-7	10 - 30
Calcium carbonate	471-34-1	10 - 30
Aluminum	7429-90-5	1 - 5
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Castor oil, hydrogenated	8001-78-3	1 - 5
Organophilic Clay	71011-26-2	1 - 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.



IDH number: 702088

Product name: Fixmaster Fast Set Steel Putty

Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Keep individual calm. DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	121 °C (249.8 °F) Tagliabue closed cup
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Use water spray to keep fire exposed containers cool and disperse vapors.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Ammonia.
Sensitivity to Mechanical Impact:	Not available.
Sensitivity to static discharge:	Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Clean residue with soap and water.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polymercaptan hardener	None	None	None	None
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.3 mg/m ³ TWA Total dust.	None	None
Calcium carbonate	10 mg/m ³ TWA Total dust.	5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust.	None	None
Aluminum	1 mg/m ³ TWA Respirable fraction.	15 mg/m ³ TWA (as Al) Total dust. 5 mg/m ³ TWA (as Al) Respirable dust.	None	None
2,4,6-Tris(dimethylaminomethyl)phenol	None	None	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ TWA Total dust.	None	None
Castor oil, hydrogenated	None	None	None	None
Organophilic Clay	None	None	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Not normally required. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	White
Odor:	Pungent
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not determined
Boiling point/range:	199 °C (390.2 °F)
Melting point/ range:	Not available.
Specific gravity:	1.7551
Vapor density:	Heavier than air.
Flash point:	121 °C (249.8 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Slower than butyl acetate.
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1.0 % (value for resin and hardener together) (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Ammonia.
Incompatible materials:	Strong bases. Strong oxidizing agents. Chlorinated rubber. Reaction with epoxy resins and/or isocyanates in large amounts or under uncontrolled conditions releases considerable heat and may release acid fumes.
Conditions to avoid:	Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Toxicologically synergistic products: Not available.

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Polymercaptan hardener	No	No	No	No
Quartz (SiO ₂)	Known To Be Human Carcinogen.	Group 1	No	Group A2
Calcium carbonate	No	No	No	No
Aluminum	No	No	No	Group A4
2,4,6-Tris(dimethylaminomethyl)phenol	No	No	No	No
Titanium dioxide	No	Group 2B	No	Group A4
Castor oil, hydrogenated	No	No	No	No
Organophilic Clay	No	No	No	No

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Polymercaptan hardener	None	No Records
Quartz (SiO ₂)	None	Immune system, Lung, Some evidence of carcinogenicity
Calcium carbonate	Oral LD50 (RAT) = 6,450 mg/kg	Nuisance dust
Aluminum	None	Central nervous system, Irritant, Lung
2,4,6-Tris(dimethylaminomethyl)phenol	None	Irritant, Allergen
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Castor oil, hydrogenated	None	No Target Organs
Organophilic Clay	None	No Target Organs

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Gary Pierson, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.