

(11187)

AkzoNobel Canada Inc.
8200 KEELE STREET
CONCORD, ONTARIO; L4K 2A5
CANADA

PRODUCT: X-PERT Striping Paint (White 20.18290.093 & Yellow 20.18291.

WHITE



Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER MANUFACTURED FOR:
AkzoNobel Canada Inc.
8200 KEELE STREET
CONCORD
ONTARIO
CANADA
L4K 2A5
905-669-1020
PRODUCT NAME..... X-PERT Striping Paint (White 20.18290.093 & Yellow 20.18291.
CHEMICAL FAMILY..... ALKYD BASED COATING.
PRODUCT CODE(S)..... 20-18290.093, 20.18291.093 .
MOLECULAR WEIGHT..... NOT APPLICABLE.
CHEMICAL FORMULA..... MIXTURE.
TRADE NAMES & SYNONYMS..... X-PERT Striping Paint (White 20.18290.093 & Yellow 20.18291.
PRODUCT USES..... COATING.
FORMULA/LAB BOOK #..... STRIPING PAINT.

APPROVED MATERIAL

MAY 03 2012

MSDS # 11187

APPROVED BY [Signature]

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Table with 6 columns: Hazardous Ingredients, %, Exposure Limit, C.A.S.#, LD/50, Route, Species, LC/50 Route, Species. Rows include ACETONE, TOLUENE, XYLENE, ETHYLBENZENE, TITANIUM DIOXIDE, TALC (MAGNESIUM SILICATE HYDRATE), ISOBUTANE, PROPANE.

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.
INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIAN.
EYE CONTACT..... MAY CAUSE IRRITATION.
SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.
SKIN CONTACT..... MAY CAUSE IRRITATION.
EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.
EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS
EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... 465 - 527.
SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.
FLAMMABILITY..... EXTREMELY FLAMMABLE.
IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
UPPER FLAMMABLE LIMIT..... 12.8.
(% BY VOLUME)

PRODUCT: X-PERT Striping Paint (White 20.18290.093 & Yellow 20.18291.

Section 05: FIRE FIGHTING MEASURES

LOWER FLAMMABLE LIMIT..... 1.
(% BY VOLUME)
EXPLOSION DATA
SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.
SENSITIVITY TO IMPACT..... NOT APPLICABLE.
HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
AEROSOL FLAME PROJECTION
CLASSIFIED AS:..... >15cm BUT <100cm.
FLASHBACK..... NONE.
FLASH POINT(°C),TAG CLOSED-CUP LOWEST KNOWN VALUE IS ACETONE @-18C.
(CONCENTRATE)

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
EYE/TYPE..... SAFETY GLASSES.
FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL
APPEARANCE..... VARIOUS COLOURS.
ODOR..... KETONE.
ODOR THRESHOLD..... NOT AVAILABLE.
VAPOUR PRESSURE(PSIG)-AEROSOL..... 55 - 65.
@ 20 C
BOILING POINT (°C)(CONC)..... 57-143.
EVAPORATION RATE..... GREATER THAN 1.
n-BUTYL ACETATE = 1
VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
(BY WEIGHT)
SOLUBILITY IN WATER g/L (20°C)..... NOT AVAILABLE.
pH..... NOT APPLICABLE.
SPECIFIC GRAVITY (LIQUID)..... 0.94-0.98.
COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
FREEZING POINT: (°C)..... NOT AVAILABLE.
AEROSOL PERCENT VOLATILE..... 72-73.
(BY WEIGHT).
SPECIFIC GRAVITY (AEROSOL)..... 0.80-0.84.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CHEMICAL STABILITY:
YES..... UNDER NORMAL CONDITIONS.
NO, WHICH CONDITIONS?..... NOT APPLICABLE.
COMPATIBILITY WITH OTHER SUBSTANCES:
NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
REACTIVITY CONDITIONS?..... NOT APPLICABLE.
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE ADVERSE FETAL DEVELOPMENTAL EFFECTS. XYLENE - HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT LEVELS TOXIC TO THE MOTHER, AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.
IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.

PRODUCT: X-PERT Striping Paint (White 20.18290.093 & Yellow 20.18291.

Section 11: TOXICOLOGICAL INFORMATION

CARCINOGENICITY/MUTAGENICITY..... XYLENE - THIS PRODUCT CONTAINS ETHYLBENZENE (ETHYLBENZENE IS IN XYLENE). ETHYLBENZENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS. TOXICITY TESTS CARRIED OUT FOR CHRONIC EFFECTS AND MUTAGENICITY HAVE BEEN NEGATIVE. THE RELEVANCE OF THIS FINDING TO HUMANS IS UNCERTAIN. IARC HAS CLASSIFIED ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN.

TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D2A,D2B.
CNFC SECTION 3.3.5..... LEVEL 2.
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.
HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.
HMIS RATING PERSONAL PROTECTION..... B.
NFPA CODE 30B..... LEVEL 2.
SARA 313 INFORMATION..... THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:
CAS #: CHEMICAL NAME:
*1330-20-7 XYLENE
*100-41-4 ETHYL BENZENE
*108-88-3 TOLUENE

CALIFORNIA PROPOSITION 65..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CAS #: CHEMICAL NAME:
*100-41-4 ETHYL BENZENE IN XYLENE
*108-88-3 TOLUENE

TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.

V.O.C.(M.I.R.)..... COMPLIES WITH TRAFFIC PAINT / MARKING PAINT CATEGORY <1.2 g ozone / g product.

Section 16: OTHER INFORMATION

NOTICE FROM ICI CANADA INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY ICI CANADA INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. ICI CANADA INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES
PREPARATION DATE Apr 15/12