



if it matters, we're on it.®

# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

**Product ID:** 610R15B  
**Product Name:** HI BUILD WASH PRIMER COMP  
**Product Use:** Paint product.  
**Effective date:** 08/Dec/2011  
**Revision Date:** 08/Dec/2011  
**UN ID Number (msds):** UN1263  
**WHMIS Classification:** D2B Toxic Material D2A Very Toxic Material B2 Flammable Liquids

### Company Identification

Valspar, Inc.  
 1915 Second Street West  
 Cornwall , Ontario K6H 5T1

**Tech Info Phone:** 1-613-932-8960

**24-Hour Medical Emergency Phone:** 1-888-345-5732

## 2. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
 Ingestion  
 Skin absorption

### Eye Contact:

- Causes severe eye burns.
- Risk of serious damage to eyes.

### Skin Contact:

- Causes skin burns.

### Ingestion:

- Causes digestive tract burns.
- Harmful if swallowed.

**APPROVED MATERIAL**  
 JUL 13 2012  
 MSDS # 11239  
 APPROVED BY *[Signature]*

- May cause damage of gastrointestinal tract.

**Inhalation:**

- Causes respiratory tract irritation.
- Harmful by inhalation.

**Acute Other Health Effects:**

- Contains ingredients which are corrosive.

**Target Organ and Other Health Effects:**

- Causes headache, drowsiness or other effects to the central nervous system.
- Liver injury may occur.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name	CAS Number
ISOPROPYL ALCOHOL 67-63-0	85 - 90	Isopropyl alcohol	67-63-0
ETHANOL 64-17-5	5 - 10	Ethyl alcohol	64-17-5
PHOSPHORIC ACID 7664-38-2	5 - 10	Phosphoric acid	7664-38-2

If this section is blank there are no hazardous components per WHMIS guidelines.

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.**

**4. FIRST AID MEASURES**

**Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Do not use soap. If skin surface is damaged, apply a clean dressing. Do not apply greases or ointments. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Ingestion:**

Give one or two glasses of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately. Rinse mouth with water. Only induce vomiting at the instruction of medical personnel.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	50
Flash point (Celsius):	10
Lower explosive limit (%):	2
Upper explosive limit (%):	21
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

### Unusual fire and explosion hazards:

None known.

### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

### Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid all personal contact.

## 7. HANDLING AND STORAGE

### Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### Other Personnel Protection Data:

Ensure that eyewash stations and safety showers are close to the workstation location. To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
ISOPROPYL ALCOHOL 67-63-0	85 - 90	400 ppm TWA 980 mg/m <sup>3</sup> TWA		
ETHANOL 64-17-5	5 - 10	1000 ppm TWA 1900 mg/m <sup>3</sup> TWA		
PHOSPHORIC ACID 7664-38-2	5 - 10	1 mg/m <sup>3</sup> TWA		

**ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
ISOPROPYL ALCOHOL 67-63-0	85 - 90	200 ppm TWA	400 ppm STEL		
ETHANOL 64-17-5	5 - 10	1000 ppm	1000 ppm STEL		
PHOSPHORIC ACID 7664-38-2	5 - 10	1 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> STEL		

**9. PHYSICAL PROPERTIES**

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	43.0827068 mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	2.07
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	6.81
Specific Gravity:	.82
Evaporation rate (butyl acetate = 1.0):	3.3
Flash point (Fahrenheit):	50
Flash point (Celsius):	10
Lower explosive limit (%):	2
Upper explosive limit (%):	21
Autoignition temperature:	not determined

**10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions.
------------	---------------------------------

## 10. STABILITY AND REACTIVITY

Conditions to Avoid:

Incompatibility:

Hazardous Polymerization:

Hazardous Decomposition Products:

Heat.

Strong oxidizing agents

None anticipated.

Carbon monoxide and carbon dioxide. Oxides of phosphorus

Sensitivity to static discharge:

Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
ISOPROPYL ALCOHOL 67-63-0	85 - 90	= 12800 mg/kg Dermal LD50 Rat = 12870 mg/kg Dermal LD50 Rabbit = 4396 mg/kg Oral LD50 Rat = 72.6 mg/L Inhalation LC50 Rat 4 h
ETHANOL 64-17-5	5 - 10	= 7060 mg/kg Oral LD50 Rat
PHOSPHORIC ACID 7664-38-2	5 - 10	= 1530 mg/kg Oral LD50 Rat = 2730 mg/kg Dermal LD50 Rabbit > 850 mg/m <sup>3</sup> Inhalation LC50 Rat 1 h

Mutagens/Teratogens/Carcinogens: None known.

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
ETHANOL 64-17-5	5 - 10			male mice-inadequate; female mice-inadequate

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
ETHANOL 64-17-5	5 - 10			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

## 14. TRANSPORTATION INFORMATION

### Canadian Transport of Dangerous Goods

Proper Shipping Name: PAINT  
Hazard Class: 3  
UN ID Number (msds): UN1263  
Packing Group: II

**TDG Clear Language Exceptions:**

For Dangerous Goods, the supplier may apply one of the following exceptions (TDG Reference): Limited quantity/Consumer Commodity (1.17), Does not sustain combustion, etc. (2.18), Viscous liquid (2.19), Flammable liquid General Exemption (1.33) or US DOT Reciprocity (9.1,3 & 4). Please consult current TDG regulations before applying any of these exceptions to subsequent shipments.

**International Air Transport Association (IATA):**

Proper Shipping Name: Paint  
 Hazard Class: 3  
 UN ID Number (msds): UN1263  
 Packing Group: II

**International Maritime Organization (IMO):**

Proper Shipping Name: PAINT  
 Hazard Class: 3  
 IMO UN/ID Number (msds): UN1263  
 Packing Group: II

**15. REGULATORY INFORMATION****INTERNATIONAL REGULATIONS - Chemical Inventories****Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada National Pollutant Release Inventory:**

Ingredient Name CAS-No.	Approx. Weight %	NPRI Status
ISOPROPYL ALCOHOL 67-63-0	85 - 90	Part 1, Group 1 Substance Part 5 Substance Part 1, Group 1 Substance
ETHANOL 64-17-5	5 - 10	Part 5 Substance
PHOSPHORIC ACID 7664-38-2	5 - 10	YES

**16. OTHER INFORMATION****HMIS Codes**

Health: 3\*  
 Flammability: 3  
 Reactivity: 1  
 PPE: X - See Section 8 for Personal Protective Equipment (PPE).

## 16. OTHER INFORMATION

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

### Preparation Information:

Prepared By: Regulatory Affairs Department  
Print date: 08/Dec/2011  
Revision Date: 08/Dec/2011

### Technical Information:

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440  
Tech Info Phone: 1-613-932-8960

**24-Hour Medical Emergency Phone:** 1-888-345-5732