

(11256)

11/08/12

MATERIAL SAFETY DATA SHEET

Page 1 of 4

MANUFACTURER'S NAME:  
Williams-Hayward Protective Coatings, Inc  
7425 West 59th Street  
Summit, IL 60501

EMERGENCY TELEPHONE:  
800-424-9300

INFORMATION TELEPHONE:  
708-458-0015

EFFECTIVE DATE: 09/28/12

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER : 12-11619NS  
PRODUCT NAME : NO-VOC NON SKID GRAY  
CHEMICAL NAME : ORGANIC COATING  
CHEMICAL FAMILY: WATER BORNE EMULSION T.C.  
HMIS RATING: H F R PP  
2 0 0 J

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT DESCRIPTION	CAS NUMBER	PERCENT BY WGT	ACGIH TLV	OSHA PEL AND OTHER EXPOSURE LIMITS
WATER (NON-HAZARDOUS)	7732-18-5		NR	NR

RCRA TRACE ELEMENTS

SECTION III - PHYSICAL DATA

BOILING RANGE: 212 TO 999 (deg F) % VOLATILE (VOLUME): 58.17  
100 TO 537 (deg C) % NVM (WEIGHT) : 63.84  
VAPOR DENSITY: HEAVIER THAN AIR % NVM (VOLUME) : 41.82  
EVAP RATE : SLOWER THAN BUTYL ACETATE  
DENSITY : 12.91 (lb/gl) VOC (less water): .04 (lb/gl)  
: 1.54 (kg/l) : 5.03 (gr/l)  
SOLVENTS : 8.363 (lb/gl) VOC (as shipped): .01 (lb/gl)  
: 1.00 (kg/l) : 2.27 (gr/l)  
APPEARANCE : GRAY IN COLOR  
ODOR : SLIGHT AMINE ODOR  
WATER SOLUBLE: YES

APPROVED MATERIAL  
OCT 29 2014  
MSDS # 11256  
APPROVED BY *[Signature]*

---

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

---

FLAMMABILITY CLASSIFICATION: PAINT, NON FLAMMABLE LIQUID

FLASH POINT: NOT APPLICABLE    LEL: N/A    UEL: N/A

EXTINGUISHING MEDIA:

For dried film: Carbon Dioxide, dry chemical and water fog.

UNUSUAL FIRE AND EXPLOSION DATA:

Acrylic emulsions will not burn. They may splatter if temperature exceeds boiling point (212 degrees F, 100 degrees C). Dried polymer films are capable of burning.

---

SECTION V - HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE:

INHALATION: Vapor or mist can cause headache, nausea, and irritation of the nose, throat, and lungs. Overexposure can have narcotic effect

EYE CONTACT: Slightly irritating to eyes.

SKIN CONTACT: Irritating to skin upon repeated or prolonged contact.

PRIMARY ROUTES OF ENTRY: Dermal, Inhalation, Ingestion.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Allergy, Asthma, Bronchitis, Emphysema.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION    Remove to fresh air. If not breathing, give artificial respiration. Have a trained person administer oxygen. CALL A PHYSICIAN.

EYE CONTACT    Wash with plenty of water for 5 minutes.

SKIN CONTACT    Wash with soap and water. An emollient cream or lotion is beneficial.

INGESTION    DO NOT SWALLOW. If swallowed, do not induce vomiting. CALL A PHYSICIAN.

---

SECTION VI - REACTIVITY DATA

---

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition may yield oxides of carbon, oxides of nitrogen and low molecular weight hydrocarbons. In baking systems, formaldehyde and ammonia may be present.

CONDITIONS TO AVOID: Non Applicable.

INCOMPATIBILITY (MATERIALS TO AVOID):

Avoid contact with strong oxidizing agents.

---

SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep unnecessary people away. Dike and contain spill with inert material (dry sand, fuller's earth, etc) and transfer the liquid to containers for recovery or proper disposal. Floor may be slippery. Care should be exercised to avoid falls.

NOTE: Emulsions can be coagulated by stepwise addition of lime and ferric sulfate to clear water end point.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state, and federal regulations.

---

SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

RESPIRATORY PROTECTION:

Follow OSHA Regulation 29CFR 1910.134 for Respiratory use. Use air-purifying respirator that respirator supplier has demonstrated to be effective for solvent vapors, when concentrations exceed the TLV up to the maximum level at which the respirator is effective. If the concentration of solvents is not known or exceeds the level at which the air-purifying respirator is effective, a positive pressure air supplied respirator (TC19C NIOSH/MSHA) is recommended.

VENTILATION:

Mechanical Local exhaust at point of contaminant (vapor, mist, or dust) release.

PROTECTIVE GLOVES:

Usual hand protection for paint application

EYE PROTECTION:

Splash-proof safety goggles (ANSI Z87.1, 1968).

OTHER PROTECTIVE EQUIPMENT:

Eyewash station, emergency shower.

