

(11257)

Material Safety Data Sheet



Revision Number: 001.1

Issue date: 03/30/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite® SF™ 7900 Ceramic Shiel
Product use: Coating

IDH number: 1616692
Item number: 1616692
Region: Canada

Company address:
Henkel Canada Corporation
2515 Meadowpine Boulevard
Mississauga, Ontario L5N 6C3

Contact information:
Telephone: 905.814.6511
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Liquid
Color: White
Odor: Solvent

WHMIS hazard class: A, B.1, D.2.B

DANGER: EXTREMELY FLAMMABLE.
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.

Relevant routes of exposure: Skin, inhalation, Eyes

Potential Health Effects

Inhalation: This product is irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
Skin contact: This product is irritating to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.
Eye contact: This product is irritating to the eyes.
Ingestion: May cause gastrointestinal tract irritation if swallowed. May cause dizziness, incoordination, headache, nausea, and vomiting.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.


See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Table with 3 columns: Hazardous components, CAS NUMBER, %

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.



IDH number: 1616692

Page 1 of 5

Product name: Loctite® SF™ 7900 Ceramic Shiel

<b>Skin contact:</b>	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Get immediate medical attention. Do not induce vomiting.
<b>Notes to physician:</b>	Treat symptomatically and supportively.

## 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	-20 °C (-4°F)
<b>Autoignition temperature:</b>	465 °C (869°F)
<b>Flammable/Explosive limits - lower:</b>	2.2 %
<b>Flammable/Explosive limits - upper:</b>	13 %
<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear full protective clothing. Wear self-contained breathing apparatus.
<b>Unusual fire or explosion hazards:</b>	DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors are heavier than air and may travel to ignition sources and flash back. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
<b>Sensitivity to Mechanical Impact:</b>	Not available.
<b>Sensitivity to static discharge:</b>	Not available.

## 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

<b>Environmental precautions:</b>	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only.
<b>Storage:</b>	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Do not store with oxidizing materials.

**For information on product shelf life contact Henkel Canada Customer Service at (905) 814-6511.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Propane/Isobutane	None	None	None	None
Acetone	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m <sup>3</sup> ) TWA	None	None
Methyl ethyl ketone	200 ppm TWA 300 ppm STEL	200 ppm (590 mg/m <sup>3</sup> ) TWA	None	None
Boron nitride	None	None	None	None

<b>Engineering controls:</b>	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
<b>Respiratory protection:</b>	If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.
<b>Eye/face protection:</b>	Wear safety glasses; chemical goggles (if splashing is possible).
<b>Skin protection:</b>	Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	White
<b>Odor:</b>	Solvent
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	6 - 8
<b>Vapor pressure:</b>	231 mm hg
<b>Boiling point/range:</b>	56 °C (132.8 °F)
<b>Melting point/ range:</b>	-95 °C (-139°F)
<b>Specific gravity:</b>	1.2
<b>Vapor density:</b>	2.0
<b>Flash point:</b>	-20 °C (-4°F)
<b>Flammable/Explosive limits - lower:</b>	2.2 %
<b>Flammable/Explosive limits - upper:</b>	13 %
<b>Autoignition temperature:</b>	465 °C (869°F)
<b>Evaporation rate:</b>	14.4
<b>Solubility in water:</b>	Soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	778 g/l (calculated)

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
<b>Incompatible materials:</b>	This product may react with oxidizing agents.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicologically synergistic products:</b>	Not available.
--	----------------

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Propane/isobutane	No	No	No	No
Acetone	No	No	No	Group A4
Methyl ethyl ketone	No	No	No	No
Boron nitride	No	No	No	No

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Propane/isobutane	None	No Records
Acetone	Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (rabbit) = 5,340 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (rabbit) = 20,000 mg/kg Dermal LD50 (rabbit) = 20 mg/kg Inhalation LC50 (RAT, 4 h) = 76 mg/l Inhalation LC50 (RAT, 8 h) = 50.1 mg/l	Blood, Central nervous system, Irritant, Reproductive
Methyl ethyl ketone	Oral LD50 (RAT) = 2,300 - 3,500 mg/kg Oral LD50 (RAT) = 4,500 - 6,800 mg/kg Dermal LD50 (rabbit) > 8,000 mg/kg Inhalation LC50 (RAT, 4 h) = 11,700 mg/l	Irritant, Central nervous system
Boron nitride	None	Irritant, Corrosive

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

### Canada Transportation of Dangerous Goods - Ground

Proper shipping name: AEROSOLS  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Mark Mau, Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henke!") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.