

(11270)

ICI CANADA INC.
8200 KEELE STREET
CONCORD, ONTARIO; L4K 2A5
CANADA

PRODUCT: X-PERT Lacquer Spray Paint 300.126.093/300.119.093



Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER MANUFACTURED FOR:
ICI CANADA INC.
8200 KEELE STREET
CONCORD
ONTARIO
CANADA
L4K 2A5
905-669-1020
PRODUCT NAME..... X-PERT Lacquer Spray Paint 300.126.093/300.119.093
CHEMICAL FAMILY..... ACRYLIC BASED COATING.
PRODUCT CODE(S)..... 300.119.093, 300.126.093.
MOLECULAR WEIGHT..... NOT APPLICABLE.
CHEMICAL FORMULA..... MIXTURE.
TRADE NAMES & SYNONYMS..... X-PERT Lacquer Spray Paint 300.126.093/300.119.093
PRODUCT USES..... COATING.
FORMULA/LAB BOOK #

APPROVED MATERIAL
JUL 24 2013
MSDS # 11270
APPROVED BY [Signature]

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Table with 6 columns: Hazardous Ingredients, %, Exposure Limit, C.A.S.#, LD/50, Route, Species, LC/50 Route, Species. Rows include ACETONE, TOLUENE, PROPYLENE GLYCOL METHYL ETHER ACETATE, DIACETONE ALCOHOL, PROPYLENE GLYCOL METHYL ETHER, n-BUTYL ACETATE, CARBON BLACK, PROPANE, and ISOBUTANE.

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.
INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIAN.
EYE CONTACT..... MAY CAUSE IRRITATION.
SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.
SKIN CONTACT..... MAY CAUSE IRRITATION.
EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.
EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS
EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... 272-480.
SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.
FLAMMABILITY..... EXTREMELY FLAMMABLE.
IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

PRODUCT: X-PERT Lacquer Spray Paint 300.126.093/300.119.093

Section 05: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
 FLASH POINT (C), TAG CLOSED CUP..... LOWEST KNOWN VALUE IS ACETONE @ -18C.
 UPPER FLAMMABLE LIMIT..... 15.1.
 (% BY VOLUME)
 LOWER FLAMMABLE LIMIT..... 1.0.
 (% BY VOLUME)
 EXPLOSION DATA
 SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.
 SENSITIVITY TO IMPACT..... NOT APPLICABLE.
 HAZARDOUS COMBUSTION
 PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS
 INCOMPLETE.
 AEROSOL FLAME PROJECTION
 CLASSIFIED AS:..... >15cm BUT <100cm.
 FLASHBACK..... NONE.

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND
 NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
 HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR
 (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
 EYE/TYPE..... SAFETY GLASSES.
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
 OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... CLEAR LIQUID.
 ODOR..... KETONE.
 ODOR THRESHOLD..... NOT AVAILABLE.
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 55-65.
 @ 20 C
 BOILING POINT (°C)(CONC)..... 57-168.
 EVAPORATION RATE..... GREATER THAN 1.
 n-BUTYL ACETATE = 1
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
 (BY WEIGHT)
 SOLUBILITY IN WATER g/L (20°C)..... NOT AVAILABLE.
 pH..... NOT APPLICABLE.
 SPECIFIC GRAVITY (LIQUID)..... 0.87-0.91.
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
 FREEZING POINT: (°C)..... NOT AVAILABLE.
 AEROSOL PERCENT VOLATILE..... 90-91.
 (BY WEIGHT)
 SPECIFIC GRAVITY (AEROSOL)..... 0.73-0.77.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF
 DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS
 INCOMPLETE.
 CHEMICAL STABILITY:
 YES..... UNDER NORMAL CONDITIONS.
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.
 COMPATIBILITY WITH OTHER SUBSTANCES:
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE
 (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE
 ADVERSE FETAL DEVELOPMENTAL EFFECTS.
 IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
 SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.

PRODUCT: X-PERT Lacquer Spray Paint 300.126.093/300.119.093

Section 11: TOXICOLOGICAL INFORMATION

CARCINOGENICITY OF MATERIAL..... THE INGREDIENTS OF THIS PRODUCT ARE NOT LISTED AS CARCINOGENS BY NTP, (NATIONAL TOXICOLOGY PROGRAM), NOT REGULATED AS CARCINOGENS BY OSHA, (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION), AND HAVE NOT BEEN EVALUATED BY IARC, (INTERNATIONAL AGENCY FOR RESEARCH ON CANCER), NOR BY ACGIH (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS).

TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.

MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A, B5, D2A, D2B.
CNFC SECTION 3.3.5..... LEVEL 2.
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.
HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.
HMIS RATING PERSONAL PROTECTION..... B.
NFPA CODE 30B..... LEVEL 2.
SARA 313 INFORMATION..... THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:
CAS #: CHEMICAL NAME:
*108-88-3 TOLUENE

CALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.

V.O.C.(M.I.R.)..... COMPLIES WITH CLEAR COATING REGULATION <1.50 g OZONE / g PRODUCT.

Section 16: OTHER INFORMATION

NOTICE FROM ICI CANADA INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY ICI CANADA INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. ICI CANADA INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES
PREPARATION DATE Jan14/11