



Material Safety Data Sheet

CHEMTREC Transportation Emergency Phone:
800-424-9300

Pittsburgh Poison Control Center Health
Emergency No.: 412-681-6669

NOTE: The CHEMTREC Transportation Emergency
Phone is to be used only in the event of chemical
emergencies involving a spill, leak, fire, exposure, or
accident involving chemicals

1. Identification

Product Name: THINNER #76 Revision Date: 3/28/2013
 Identification Number: 0576S1NL Supercedes Date: 10/4/2012
 Product Use/Class: FOR INDUSTRIAL USE ONLY
 Manufacturer: Carboline Company Preparer: Regulatory Department
 2150 Schuetz Road
 St. Louis, MO 63146
 800-848-4645

2. Hazard Identification

EMERGENCY OVERVIEW: Irritating to eyes and skin. **WARNING! - FLAMMABLE LIQUID AND VAPOUR.** Keep away from heat and sources of ignition. Harmful if inhaled. Use with adequate ventilation. Vapours may cause drowsiness and dizziness. Keep container closed. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Harmful if swallowed. Risk of serious damage to the lungs (by aspiration).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Vapours may be irritating to eyes, nose, throat, and lungs.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

MEDICAL CONDITIONS PRONE TO AGGRAVATION: No information available.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

3. Composition/Information On Ingredients

Hazardous Ingredients

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|---------------------|---------|-----------------------|-------------------|--------------------|--------------|----------------------|
| METHYL ETHYL KETONE | 78-93-3 | 100.0 | 200 PPM | 300 PPM | 590 MGM3 | N/E |

4. First-aid Measures

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER SKIN CONTACT: If skin irritation persists, call a physician. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

5. Fire-fighting Measures

| | | | |
|---------------------------------|---|---------------------------|------|
| Flash Point, °F: (Setaflash) | 21F (-6C) | Lower Explosive Limit, %: | 1.8 |
| | | Upper Explosive Limit, %: | 10.1 |
| Extinguishing Media: | Carbon Dioxide, Dry Chemical, Foam, Water Fog | | |

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source.* Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

6. Accidental Release Measures

PERSONAL SAFETY MEASURES/ENVIRONMENTAL MEASURES/METHOD OF CLEANING/CONTAINMENT: Do not allow material to contaminate ground water system. Prevent product from entering drains. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Evacuate personnel to safe areas. Wear personal protective equipment. For personal protection see section 8. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

7. Handling and Storage

INSTRUCTIONS FOR SAFE HANDLING : Do not get in eyes, on skin, or on clothing. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist.

STORAGE CONDITIONS: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

RESPIRATORY PROTECTION: Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

SKIN PROTECTION: Lightweight protective clothing Impervious gloves Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Request information on glove permeation properties from the glove supplier.

EYE PROTECTION: Safety glasses with side-shields

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

PROTECTION AND HYGIENE MEASURES : Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

| | | | |
|----------------------|-----------------------------|-------------------|-------------------|
| Boiling Range: | 172 F (77 C) - 178 F (81 C) | Vapor Density: | Heavier than Air |
| Odor: | Ketone | Odor Threshold: | N/D |
| Appearance: | Clear Liquid | Evaporation Rate: | Slower Than Ether |
| Solubility in Water: | N/D | Specific Gravity: | 0.81 |
| Freeze Point: | N/D | pH: | N/D |
| Physical State: | Liquid | Vapor Pressure: | No Information |

(See section 16 for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Heat, flames and sparks.

MATERIALS TO AVOID: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

HAZARDOUS POLYMERIZATION: Hazardous polymerisation does not occur.

STABILITY: Stable under normal conditions.

11. Toxicological Information

| Chemical Name | CAS-No. | LD50 | LC50 |
|---------------------|---------|----------------------|-----------------------------------|
| METHYL ETHYL KETONE | 78-93-3 | 2194 mg/kg rat, oral | 34.5 mg/L/ 4 hour rat, inhalation |

12. Ecological Information

ECOLOGICAL INFORMATION: No information available.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of in accordance with local regulations.

14. Transport Information

| | | | |
|---------------------------|------------------------|-------------------|-----|
| DOT Proper Shipping Name: | Paint Related Material | Packing Group: | II |
| DOT Technical Name: | N/A | Hazard Subclass: | N/A |
| DOT Hazard Class: | 3 | Resp. Guide Page: | 128 |
| DOT UN/NA Number: | UN 1263 | | |
| Additional Notes: | No Information | | |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations:

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS Class: B2 D2B

16. Other Information

HMIS Ratings:

Health: 2 Flammability: 3 Reactivity: 0 Personal Protection: X

VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNED): 804

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

